

ALPHA WIRE

CUSTOMER PRODUCT SPECIFICATION

Part Number: SF61114CY
Page 1 of 2 Pages

Issue: 4
Issue Date: 10/13/2011
Effective Date: 11/4/2011

A. Construction

Diameters (In)

- | | | |
|----------------|---|-------|
| 1) Component 1 | 4 X 1 COND | |
| a) Conductor | 14 (41/30) AWG TC | 0.074 |
| b) Insulation | 0.016" Wall, Nom. PVC/ 0.005" Wall NYLON | 0.116 |
| (1) Print | ALPHANUMERIC NUMBERS - 1-ONE ALTERNATING AND INVERTED | |
| (2) Color Code | Alpha Wire Color Code KX | |

Cond	Color	Cond	Color	Cond	Color
1	GREEN/YELLOW	3	BLACK#2		
2	BLACK#1	4	BLACK#3		

- | | | |
|---------------------|--|-----------------|
| 2) Cable Assembly | 4 Components Cabled | |
| a) Twists: | 4.0 Twists/foot (min) | |
| b) Core Wrap | REMAI Tape, 25% Overlap, Min. | |
| 3) Shield: | A/P/A Tape, 25% Overlap, Min. | |
| a) Drain Wire | 20 (19/32) AWG TC | |
| b) Braid | TC, 70% Coverage, Min. | |
| 4) Jacket | 0.055" Wall, Nom., TPE | 0.442 +/- 0.020 |
| a) Color(s) | ORANGE | |
| b) Jacket Separator | Tissue Tape, 25% Overlap, Min. | |
| c) Print | ALPHA WIRE-* P/N SF61114CY 4C 14 AWG
THHN E324185 (UL) WTTC 90C 1000 VOLT OR (UL)
TC-ER 90C 600V OIL RES I/II SUN RES OR C(UL) CIC
CONTROL/TC 90C PVC/NYLON INS FT4 14 AWG
--- LLXXXXXX CSA AWM I/II A/B 90C 600V FT4
CE ROHS (DATE CODE) (SEQ FOOTAGE)
* = Factory Code | |

[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]

B. Applicable Specifications

- | | | |
|----------------------|-----------------------------------|------------------------------|
| 1) UL | | |
| a) Component 1 | THHN | 90°C / 600 V _{RMS} |
| b) Overall | TC | 90°C / 600 V _{RMS} |
| | EXPOSED RUN | |
| | OIL RES I/II | |
| | SUN RES | |
| | WTTC | 90°C / 1000 V _{RMS} |
| 2) CSA International | AWM I/II A/B | 90°C / 600 V _{RMS} |
| | FT4 | |
| | C(UL) CIC CONTROL | 90°C / 600 V _{RMS} |
| | C(UL) TC | 90°C / 600 V _{RMS} |
| 3) CE: | LVD 73/23/EEC Amendment 93/68/EEC | |

C. Environmental Compliance

- EU Directive 2002/95/EC(RoHS):
All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.
- California Proposition 65:
The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

D. Physical & Mechanical Properties

- Temperature Range: -25 to 90°C(static), -5 to 90°C (dynamic)
- Bend Radius: 10X Cable Diameter
- Pull Tension: 147 Lbs, Maximum
- Sunlight Resistance: Yes

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE
CUSTOMER PRODUCT SPECIFICATION

Part Number: SF61114CY
Page 2 of 2 Pages

Issue: 4
Issue Date: 10/13/2011
Effective Date: 11/4/2011

- E. Electrical Properties** (For Engineering purposes only)
- 1) Voltage Rating 600 V_{RMS}
 - 2) Capacitance 53 pf/ft @1 kHz, Nominal Conductor to Conductor
 - 3) Ground Capacitance 95 pf/ft @1 kHz, Nominal
 - 4) Inductance 0.17 µH/ft, Nominal
 - 5) Conductor DCR 2.8 Ω/1000ft @20°C, Nominal
 - 6) OA Shield DCR 1.66 Ω/1000ft @20°C, Nominal
- F. Other**
- 1) Packaging Flange x Traverse x Barrel (inches)
 - a) 1000 FT 24 x 14 x 12 Continuous length
 - b) 500 FT 18 x 12 x 8 Continuous length
 - c) 100 FT 12 x 10 x 5 Continuous length*[Spool dimensions may vary slightly]*
 - 2) Notes:
 - a) Suitable for use in Industrial Machinery per the requirements of NFPA-79

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.