



[Home](#) Cubitron II Abrasives

[Products](#) | [Technology](#) | [Resources](#) | [Testimonials](#)

[United States](#) > [Products & Services](#) > [Manufacturing and Industry](#) > [Cubitron II](#) > [Products](#) > [Cable/Wire](#) > 3M™ Round Conductor Flat Cable, 3756 Series, 3756/40, 100 ft.

3M™ Round Conductor Flat Cable, 3756 Series, 3756/40, 100 ft.

UPC# 00051119952957 3M Product Number 3756/40 3M ID 80001138678

Print Share



.025" 30 AWG Stranded, TPE, 100 ft.

· .025 inch wire spacing increases signal density · TPE insulation provides excellent transmission properties · 30 AWG stranded conductors on .025 inch wire spacing is designed for mass termination and flexibility · Meets the SCSI-3 characteristic impedance requirements

www.facebook.com
is not loading.

Need Help?

Questions? We can help
[Contact Us](#)

[Overview](#) [Support](#)

Specifications

Color	Gray
-------	------

People who viewed this item also viewed



3M™ 4-Wall Header .100 in., High Temp Option, Straight, 30 Contacts, 3440-6302



3M™ Round Conductor Flat Cable, 3801 Series, C3801/14, 100 ft.



3M™ Round Conductor Flat Cable, 3365 Series, 3365/25, 100 ft.



3M™ High Flex Life Cable, 3319 Series, 3319/14, 100 ft.



3M™ Wiremount Plug, 4600 Series, 4620-6000