

Component connector - ST-BE-VP - 2802332

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Component plug, for 4-pos. components, two basic terminal blocks required per plug, 19 mm high



The figure shows ST-BE

Key commercial data

Packing unit	1 pc
GTIN	 4 017918 074425
Weight per Piece (excluding packing)	13.93 GRM
Custom tariff number	85366990
Country of origin	Poland

Technical data

Product type	Component plug terminal block
Approval	UL Recognized
	cUL Recognized
	GOST
	GOST

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149
eCl@ss 8.0	27141149

Component connector - ST-BE-VP - 2802332

Classifications

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002018
ETIM 5.0	EC002018

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / GOST / GOST / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized 	
mm²/AWG/kcmil	30-14
Nominal current I _N	10 A
Nominal voltage U _N	300 V

Component connector - ST-BE-VP - 2802332

Approvals

cUL Recognized 	
mm²/AWG/kcmil	30-14
Nominal current I _N	10 A
Nominal voltage U _N	300 V

GOST 
--

GOST 
--

cULus Recognized 
--

Accessories

Accessories

Documentation

Mounting material - ST-IL - 3039900

Operating decal for the ST terminal block

