


# Standard Power MOSFET

## IXTH 30N25


$$\begin{aligned} V_{DSS} &= 250 \text{ V} \\ I_{D(\text{cont})} &= 30 \text{ A} \\ R_{DS(\text{on})} &= 75 \text{ m}\Omega \end{aligned}$$

N-Channel Enhancement Mode



| Symbol                                                                          | Test Conditions                                                                                                                         | Maximum Ratings  |                  |
|---------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|------------------|------------------|
| $V_{DSS}$                                                                       | $T_J = 25^\circ\text{C to } 150^\circ\text{C}$                                                                                          | 250              | V                |
| $V_{DGR}$                                                                       | $T_J = 25^\circ\text{C to } 150^\circ\text{C}; R_{GS} = 1 \text{ M}\Omega$                                                              | 250              | V                |
| $V_{GS}$                                                                        | Continuous                                                                                                                              | $\pm 20$         | V                |
| $V_{GSM}$                                                                       | Transient                                                                                                                               | $\pm 30$         | V                |
| $I_{D25}$                                                                       | $T_C = 25^\circ\text{C}$                                                                                                                | 30               | A                |
| $I_{DM}$                                                                        | $T_C = 25^\circ\text{C}$ , pulse width limited by $T_{JM}$                                                                              | 120              | A                |
| $I_{AR}$                                                                        |                                                                                                                                         | 30               | A                |
| $E_{AR}$                                                                        | $T_C = 25^\circ\text{C}$                                                                                                                | 30               | mJ               |
| $E_{AS}$                                                                        | $T_C = 25^\circ\text{C}$                                                                                                                | 1.0              | J                |
| $dv/dt$                                                                         | $I_S \leq I_{DM}$ , $di/dt \leq 100 \text{ A}/\mu\text{s}$ , $V_{DD} \leq V_{DSS}$ ,<br>$T_J \leq 150^\circ\text{C}$ , $R_G = 2 \Omega$ | 5                | V/ns             |
| $P_D$                                                                           | $T_C = 25^\circ\text{C}$                                                                                                                | 200              | W                |
| $T_J$                                                                           |                                                                                                                                         | $-55 \dots +150$ | $^\circ\text{C}$ |
| $T_{JM}$                                                                        |                                                                                                                                         | 150              | $^\circ\text{C}$ |
| $T_{stg}$                                                                       |                                                                                                                                         | $-55 \dots +150$ | $^\circ\text{C}$ |
| $M_d$                                                                           | Mounting torque                                                                                                                         | 1.13/10          | Nm/lb.in.        |
| <b>Weight</b>                                                                   |                                                                                                                                         | 6                | g                |
| Maximum lead temperature for soldering<br>1.6 mm (0.062 in.) from case for 10 s |                                                                                                                                         | 300              | $^\circ\text{C}$ |

TO-247 AD



G = Gate, D = Drain,  
S = Source, TAB = Drain

### Features

- International standard package JEDEC TO-247 AD
- Low  $R_{DS(\text{on})}$  HDMOS™ process
- Rugged polysilicon gate cell structure
- High commutating  $dv/dt$  rating
- Fast switching times

### Applications

- Switch-mode and resonant-mode power supplies
- Motor controls
- Uninterruptible Power Supplies (UPS)
- DC choppers


### Advantages

- Easy to mount with 1 screw (isolated mounting screw hole)
- Space savings
- High power density

| Symbol              | Test Conditions                                                                                                   | Characteristic Values<br>( $T_J = 25^\circ\text{C}$ , unless otherwise specified) |      |                                       |
|---------------------|-------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------|---------------------------------------|
|                     |                                                                                                                   | min.                                                                              | typ. | max.                                  |
| $V_{DSS}$           | $V_{GS} = 0 \text{ V}$ , $I_D = 250 \mu\text{A}$                                                                  | 250                                                                               |      | V                                     |
| $V_{GS(\text{th})}$ | $V_{DS} = V_{GS}$ , $I_D = 250 \mu\text{A}$                                                                       | 2                                                                                 |      | 4 V                                   |
| $I_{GSS}$           | $V_{GS} = \pm 20 \text{ V}_{DC}$ , $V_{DS} = 0$                                                                   |                                                                                   |      | $\pm 100 \text{ nA}$                  |
| $I_{DSS}$           | $V_{DS} = V_{DSS}$<br>$V_{GS} = 0 \text{ V}$<br>$T_J = 125^\circ\text{C}$                                         |                                                                                   |      | 25 $\mu\text{A}$<br>250 $\mu\text{A}$ |
| $R_{DS(\text{on})}$ | $V_{GS} = 10 \text{ V}$ , $I_D = 15 \text{ A}$<br>Pulse test, $t \leq 300 \mu\text{s}$ , duty cycle $d \leq 2 \%$ | 55                                                                                |      | 75 $\text{m}\Omega$                   |

| Symbol       | Test Conditions                                                                                         | Characteristic Values<br>( $T_J = 25^\circ\text{C}$ , unless otherwise specified) |      |      |
|--------------|---------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------|------|
|              |                                                                                                         | min.                                                                              | typ. | max. |
| $g_{fs}$     | $V_{DS} = 10\text{ V}; I_D = 15\text{ A}$ , pulse test                                                  | 24                                                                                | 32   | S    |
| $C_{iss}$    | $V_{GS} = 0\text{ V}, V_{DS} = 25\text{ V}, f = 1\text{ MHz}$                                           | 3950                                                                              | 510  | pF   |
| $C_{oss}$    |                                                                                                         |                                                                                   |      | pF   |
| $C_{rss}$    |                                                                                                         |                                                                                   |      | pF   |
| $t_{d(on)}$  | $V_{GS} = 10\text{ V}, V_{DS} = 0.5 \cdot V_{DSS}, I_D = 30\text{ A}$<br>$R_G = 3.6\ \Omega$ (External) | 19                                                                                | 19   | ns   |
| $t_r$        |                                                                                                         |                                                                                   |      | ns   |
| $t_{d(off)}$ |                                                                                                         |                                                                                   |      | ns   |
| $t_f$        |                                                                                                         |                                                                                   |      | ns   |
| $Q_{g(on)}$  | $V_{GS} = 10\text{ V}, V_{DS} = 0.5 \cdot V_{DSS}, I_D = 0.5 I_{D25}$                                   | 136                                                                               | 32   | nC   |
| $Q_{gs}$     |                                                                                                         |                                                                                   |      | nC   |
| $Q_{gd}$     |                                                                                                         |                                                                                   |      | nC   |
| $R_{thJC}$   |                                                                                                         | 0.25                                                                              | 0.65 | K/W  |
| $R_{thCK}$   |                                                                                                         |                                                                                   |      | K/W  |

| Source-Drain Diode |                                                                                                       | Characteristic Values<br>( $T_J = 25^\circ\text{C}$ , unless otherwise specified) |      |               |
|--------------------|-------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------|---------------|
| Symbol             | Test Conditions                                                                                       | min.                                                                              | typ. | max.          |
| $I_S$              | $V_{GS} = 0\text{ V}$                                                                                 |                                                                                   |      | 30 A          |
| $I_{SM}$           | Repetitive; pulse width limited by $T_{JM}$                                                           |                                                                                   |      | 120 A         |
| $V_{SD}$           | $I_F = I_S, V_{GS} = 0\text{ V}$ ,<br>Pulse test, $t \leq 300\ \mu\text{s}$ , duty cycle $d \leq 2\%$ |                                                                                   |      | 1.5 V         |
| $t_{rr}$           | $I_F = I_S, -di/dt = 100\text{ A}/\mu\text{s}, V_R = 100\text{ V}$                                    | 300                                                                               |      | ns            |
| $Q_{rr}$           |                                                                                                       | 3.0                                                                               |      | $\mu\text{C}$ |

**TO-247 AD Outline**


Terminals: 1 - Gate 2 - Drain  
3 - Source Tab - Drain

| Dim.           | Millimeter |       | Inches |       |
|----------------|------------|-------|--------|-------|
|                | Min.       | Max.  | Min.   | Max.  |
| A              | 4.7        | 5.3   | .185   | .209  |
| A <sub>1</sub> | 2.2        | 2.54  | .087   | .102  |
| A <sub>2</sub> | 2.2        | 2.6   | .059   | .098  |
| b              | 1.0        | 1.4   | .040   | .055  |
| b <sub>1</sub> | 1.65       | 2.13  | .065   | .084  |
| b <sub>2</sub> | 2.87       | 3.12  | .113   | .123  |
| C              | .4         | .8    | .016   | .031  |
| D              | 20.80      | 21.46 | .819   | .845  |
| E              | 15.75      | 16.26 | .610   | .640  |
| e              | 5.20       | 5.72  | 0.205  | 0.225 |
| L              | 19.81      | 20.32 | .780   | .800  |
| L1             |            | 4.50  |        | .177  |
| ØP             | 3.55       | 3.65  | .140   | .144  |
| Q              | 5.89       | 6.40  | 0.232  | 0.252 |
| R              | 4.32       | 5.49  | .170   | .216  |
| S              | 6.15       | BSC   | .242   | BSC   |