





RECTIFIER DIODES, Leadless Surface Mount, Ultra Fast Recovery

ISI Part Number	Maximum Average Rectified Current at T _a		Peak Inverse Voltage	Peak Forward Surge Current @ 8.3ms Superimposed	Maximum Fwd Voltage @Rated I _F and T _a =25°C	Maximum Rev. Current @ Rated PIV and T _a =25°C	Reverse Recovery Time at Rated PIV	Package Quantities	Outline																																										
	I _F (Amps)	T _a (°C)	PIV (Volts)	I _{FSM} (Amps)	V _{FM} (Volts)	I _R (uA)	T _{RR} (nsec)	Bulk/Reel	inches/millimeters																																										
EGL34A EGL34B EGL34C EGL34D EGL34F EGL34G	0.5	75	50	10	1.25	5.0	50	2500/ NA	 <table><thead><tr><th rowspan="2">DIM</th><th colspan="3">MM</th><th colspan="3">INCHES</th></tr><tr><th>MIN</th><th>MAX</th><th></th><th>MIN</th><th>MAX</th></tr></thead><tbody><tr><td>D</td><td>1.60</td><td>1.70</td><td></td><td>.063</td><td>.067</td></tr><tr><td>F</td><td>0.41</td><td>0.55</td><td></td><td>.016</td><td>.022</td></tr><tr><td>G</td><td>3.30</td><td>3.70</td><td></td><td>.130</td><td>.146</td></tr><tr><td>S</td><td>0.20</td><td></td><td></td><td>.008</td><td></td></tr><tr><td>G1</td><td>2.44</td><td>Ref</td><td></td><td>.096</td><td>Ref</td></tr></tbody></table> DO-213AA	DIM	MM			INCHES			MIN	MAX		MIN	MAX	D	1.60	1.70		.063	.067	F	0.41	0.55		.016	.022	G	3.30	3.70		.130	.146	S	0.20			.008		G1	2.44	Ref		.096	Ref
DIM			MM								INCHES																																								
			MIN		MAX						MIN	MAX																																							
D			1.60		1.70						.063	.067																																							
F			0.41		0.55						.016	.022																																							
G			3.30		3.70						.130	.146																																							
S	0.20			.008																																															
G1	2.44	Ref		.096	Ref																																														
			100	1.25																																															
			150	1.25																																															
			200	1.25																																															
			300	1.35																																															
			400	1.35																																															
EGL41A EGL41B EGL41C EGL41D EGL41F EGL41G	1.0	75	50	30	1.0	5.0	50	1500/ 2500	 <table><thead><tr><th rowspan="2">DIM</th><th colspan="3">MM</th><th colspan="3">INCHES</th></tr><tr><th>MIN</th><th>MAX</th><th></th><th>MIN</th><th>MAX</th></tr></thead><tbody><tr><td>D</td><td>2.39</td><td>2.68</td><td></td><td>.094</td><td>.105</td></tr><tr><td>F</td><td>0.41</td><td>0.55</td><td></td><td>.016</td><td>.022</td></tr><tr><td>G</td><td>4.80</td><td>5.20</td><td></td><td>.189</td><td>.205</td></tr><tr><td>S</td><td>0.20</td><td></td><td></td><td>.008</td><td></td></tr><tr><td>G1</td><td>4.04</td><td>Ref</td><td></td><td>.159</td><td>Ref</td></tr></tbody></table> DO-213AB	DIM	MM			INCHES			MIN	MAX		MIN	MAX	D	2.39	2.68		.094	.105	F	0.41	0.55		.016	.022	G	4.80	5.20		.189	.205	S	0.20			.008		G1	4.04	Ref		.159	Ref
DIM			MM								INCHES																																								
			MIN		MAX						MIN	MAX																																							
D			2.39		2.68						.094	.105																																							
F			0.41		0.55						.016	.022																																							
G			4.80		5.20						.189	.205																																							
S	0.20			.008																																															
G1	4.04	Ref		.159	Ref																																														
			100	1.0																																															
			150	1.0																																															
			200	1.0																																															
			300	1.25																																															
			400	1.25																																															

RECTIFIER DIODES, Leadless Surface Mount, Glass Passivated, Standard Recovery

ISI Part Number	Maximum Average Rectified Current at T_A		Peak Inverse Voltage	Peak Forward Surge Current @ 8.3ms Superimposed	Maximum Fwd Voltage @ Rated I_F and $T_A=25^{\circ}\text{C}$	Maximum Rev. Current @ Rated PIV and $T_A=25^{\circ}\text{C}$	Reverse Recovery Time at Rated PIV	Package Quantities	Outline																																										
	I_F (Amps)	T_A ($^{\circ}\text{C}$)	PIV (Volts)	I_{FSM} (Amps)	V_{FS} (Volts)	I_R (μA)	T_{RR} (nsec)	Bulk/Reel	inches/millimeters																																										
GL34A GL34B GL34D GL34G GL34J	0.5	75	50	10	1.1	5.0	N/A	2500/ NA	 <table><thead><tr><th colspan="3">MM</th><th colspan="3">INCHES</th></tr><tr><th>DIM</th><th>MIN</th><th>MAX</th><th>MIN</th><th>MAX</th><th></th></tr></thead><tbody><tr><td>D</td><td>1.60</td><td>1.70</td><td>.063</td><td>.067</td><td></td></tr><tr><td>F</td><td>0.41</td><td>0.55</td><td>.016</td><td>.022</td><td></td></tr><tr><td>G</td><td>3.30</td><td>3.70</td><td>.130</td><td>.146</td><td></td></tr><tr><td>S</td><td>0.20</td><td></td><td>.008</td><td></td><td></td></tr><tr><td>G1</td><td>2.44</td><td>Ref</td><td>.096</td><td>Ref</td><td></td></tr></tbody></table> DO-213AA	MM			INCHES			DIM	MIN	MAX	MIN	MAX		D	1.60	1.70	.063	.067		F	0.41	0.55	.016	.022		G	3.30	3.70	.130	.146		S	0.20		.008			G1	2.44	Ref	.096	Ref	
MM			INCHES																																																
DIM			MIN							MAX	MIN	MAX																																							
D			1.60							1.70	.063	.067																																							
F			0.41							0.55	.016	.022																																							
G	3.30	3.70	.130	.146																																															
S	0.20		.008																																																
G1	2.44	Ref	.096	Ref																																															
1N6478 1N6479 1N6480 1N6481 1N6482 1N6483 1N6484	1.0	75	50	30	1.1	10.0	N/A	1500/ 5000	 <table><thead><tr><th colspan="3">MM</th><th colspan="3">INCHES</th></tr><tr><th>DIM</th><th>MIN</th><th>MAX</th><th>MIN</th><th>MAX</th><th></th></tr></thead><tbody><tr><td>D</td><td>2.39</td><td>2.66</td><td>.094</td><td>.105</td><td></td></tr><tr><td>F</td><td>0.41</td><td>0.55</td><td>.016</td><td>.022</td><td></td></tr><tr><td>G</td><td>4.80</td><td>5.20</td><td>.189</td><td>.205</td><td></td></tr><tr><td>S</td><td>0.20</td><td></td><td>.008</td><td></td><td></td></tr><tr><td>G1</td><td>4.04</td><td>Ref</td><td>.159</td><td>Ref</td><td></td></tr></tbody></table> DO-213AB	MM			INCHES			DIM	MIN	MAX	MIN	MAX		D	2.39	2.66	.094	.105		F	0.41	0.55	.016	.022		G	4.80	5.20	.189	.205		S	0.20		.008			G1	4.04	Ref	.159	Ref	
MM			INCHES																																																
DIM			MIN							MAX	MIN	MAX																																							
D			2.39							2.66	.094	.105																																							
F			0.41							0.55	.016	.022																																							
G			4.80							5.20	.189	.205																																							
S			0.20								.008																																								
G1			4.04	Ref	.159	Ref																																													
GL41A GL41B GL41D GL41G GL41J GL41K GL41M GL41T GL41Y			50	1.1	10.0	N/A	1500/ 5000																																												
			100	1.1																																															
	200	1.1																																																	
	400	1.1																																																	
	600	1.1																																																	
	800	1.1																																																	
	1000	1.1																																																	
	1300	1.2																																																	
	1600	1.2																																																	