

Automotive Wire

Tinned Stranded to BS4808

pro-POWER



Features:

- Plain annealed copper conductors PVC insulated to BS6862 Part 1. Resistant to petrol, lubrication oils, fuel oils and dilute acids.
- These cables are suitable for automotive, marine and agricultural applications.

Specification Table:

Part Number	6X236 BLK	6X236 RED	6X314 BLK	6X235 BLK	6X235 RED	30734
Specification	14/0.3 (1mm ²)		21/0.3 (1.5mm ²)	28/0.3 (2mm ²)		9/0.3 Twin Flat
Conductor	Plain annealed copper wire					
Number and Size of Wires	14 × 0.3		21 × 0.3	28 × 0.3		9 × 0.3
-	Test Voltage 1.5KV for 2 minutes	Test Voltage 1.5KV for 2 minutes	Test Voltage 1.5KV for 2 minutes	-	-	Nominal Dimensions 3.8 × 6.1
Current Rating (A)	8.75		13	17.5		5.75
Insulation	PVC					
Nominal Outside Diameter	2.7		3.1	3.4		2.5
Insulation Thickness	0.6					
Temperature °C	+70°C					
Resistance	20°C 18.84 (Ω/kM)		20°C 12.57 (Ω/kM)	20°C 9.42 (Ω/kM)		20°C 29.35 (Ω/kM)
Colour	Black	Red	Black		Red	Outer Sheath Red and Black Conductor Insulation
Length (m)	500					100

Part Number Table

Description	Part Number
Wire, Auto, Black, 1mm, 500m	6X236 BLK
Wire, Auto, Red, 1mm, 500m	6X236 RED
Wire, Auto, Black, 1.5mm, 500m	6X314 BLK
Wire, Auto, Black, 2mm, 500m	6X235 BLK
Wire, Auto, Red, 2mm, 500m	6X235 RED
Cable, Automotive, Twin, Flat, 100m	30734

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.