



Adjustable double thick reversible partitions allow you to fold over for longer use. Lid is included.

Features

- Shields ESD sensitive items from charge and electrostatic discharges (with lid in place).
- Provides ESD and physical protection for ESD sensitive circuit boards.
- Impregnated corrugated material; greater durability than coated or printed material.
- Constructed with double sides, double (boxes under 6" deep) or triple (boxes over 6" deep) ends, and single (boxes under 6" deep) or double (boxes over 6" deep) thickness bottom for greater durability.
- Buried shielding layer minimizing the potential of sloughing and rub-off contamination.
- Made from 100% recycled material, and is 100% recyclable
- No tooling costs.
- Easy assembly without the need for tape, glue, or staples.

[Click Here for available cell sizes](#)

Meets the required limits of ANSI/ESD S20.20, and Packaging standard ANSI/ESD S541.

SPECIFICATIONS

Properties

- Surface Resistance
- Discharge Shielding
- Sloughing Test

Recyclability

Typical Values

- 1 x 10⁶ to < 1 x 10⁹ ohms
- <10 nJ
- Negligible surface damage at 10 cycles and <5% of surface damage at 200 cycles in Taber Abrasion Test.
- No conductive particles abraded from surface
- Complete recyclability of package

Test Procedures/Method

- ANSI/ESD STM11.11
- ANSI/ESD STM 11.31
- ASTM D4060 at 70 rpm with CS-17 abrasive-coated wheels and 1000 grams load
- Rockwell International Test Report of January 8, 1992
- Rockwell International Test Report of January 8, 1992

RoHS, REACH, and Conflict Minerals Statement:
 See the Desco Industries ROHS, Reach and Conflict Minerals Statement
Descoindustries.com/ROHS3.aspx

See the Protektive Pak Limited Warranty
Protektivepak.descoindustries.com/Limited-Warranty.aspx



Made in the United States of America

CORRUGATED IN-PLANT HANDLERS



PROTEKTIVE PAK
 13520 MONTE VISTA AVENUE, CHINO, CA 91710
 PHONE (909) 627-2578
ProtektivePak.com

DRAWING NUMBER
 37150

DATE:
 December 2024