

Low Skew 4-Pair UTP

NEC Type CMR/CMP (UL), c(UL)

Product Construction:

Conductor:

- 23 or 24 AWG solid bare copper

Insulation:

- Fluorinated ethylene propylene (FEP)
- High density propylene (HDPE)

Jacket:

- Plenum - Flexguard® green
- Riser - PVC maroon

Applications:

- Suitable for RGB video applications
- Digital CCTV cameras

Compliances:

- NEC Article 800 Type CMR (UL), c(UL)
- NEC Article 800 Type CMP (UL), c(UL)

Packaging:

- 1000' Pull-Pacs®
- Contact Customer Service for additional packaging options

Color Code Chart

NO. OF PAIRS	COLOR
1	White/Blue Stripe and Blue
2	White/Orange Stripe and Orange
3	White/Green Stripe and Green
4	White/Brown Stripe and Brown

CATALOG NUMBER	AWG SIZE	NOMINAL DCR	NOMINAL O.D. (INCHES)	INSULATION MATERIAL		NOMINAL IMPEDANCE OHMS	PROPAGATION DELAY SKEW	NOMINAL ATTENUATION		BELDEN PART NO.
				INCHES	mm			MHz	dB/328 ft.	
E3842S CMP 	24 AWG Solid Bare Copper	27.4 Ω/Mft	0.185	Fluorinated Ethylene Propylene (FEP)		100	2.2 ns/328 ft.	1	2.0	7987P
								4	4.1	
								8	5.8	
								10	6.5	
								16	8.2	
				20	9.3					
				25	10.4					
				31.25	11.7					
				62.50	17.0					
				100	22.0					
				155	28.1					
				200	32.0					
				250*	36.4					
				300*	41.0					
				350*	44.8					
E1842S CMR 	24 AWG Solid Bare Copper	27.4 Ω/Mft	0.185	High Density Propylene (HDPE)		100	2.2 ns/328 ft.	1	2.0	7987R
								4	4.1	
								8	5.8	
								10	6.5	
								16	8.2	
				20	9.3					
				25	10.4					
				31.25	11.7					
				62.50	17.0					
				100	22.0					
				155	28.1					
				200	32.0					
				250*	36.4					
				300*	41.0					
				350*	44.8					
E3843S CMP 	23 AWG Solid Bare Copper	22.0 Ω/Mft	0.200	Fluorinated Ethylene Propylene (FEP)		100	2.2 ns/328 ft.	1	2.0	7989P
								4	3.8	
								8	5.3	
								10	6.0	
								16	7.6	
				20	8.5					
				25	9.5					
				31.25	10.7					
				62.50	15.4					
				100	19.8					
				155	25.2					
				200	29.0					
				250	32.8					
				300*	35.2					
				350*	39.8					
E1843S CMR 	23 AWG Solid Bare Copper	22.0 Ω/Mft	0.213	High Density Propylene (HDPE)		100	2.2 ns/328 ft.	1	2.0	7989R
								4	3.8	
								8	5.3	
								10	6.0	
								16	7.6	
				20	8.5					
				25	9.5					
				31.25	10.7					
				62.50	15.4					
				100	19.8					
				155	25.2					
				200	29.0					
				250*	32.8					
				300*	35.2					
				350*	39.8					

*For information only.

**CAROL
BRAND**

c **UL** US
LISTED

UL
Listed Type
CM

UL
Listed Type
CMP

 **General Cable**