



Telecom Performance 5x7mm TCXO / VCTCXO T / TV Series



2111 Comprehensive Drive

Aurora, Illinois 60505

Phone: 630-851-4722

Fax: 630-851-5040

www.conwin.com

US Headquarters:

630-851-4722

European Headquarters:


+353-61-472221

Description:

Connor-Winfield's Txxx and TVxxx series are 5x7mm TCXO and VCTCXO products with exceptional frequency stability and low phase noise. Through the use of analog temperature compensation, these products are capable of holding Stratum 3 level temperature stabilities of ± 0.28 ppm over the commercial and industrial temperature ranges. Available in 4-pad or 10-pad surface mount footprints.

These products are designed for such applications as IEEE 1588 PTP and Synchronous Ethernet.

All models will meet ± 4.6 ppm accuracies for twenty years



Features:

- Frequency Stabilities Available:
 ± 0.28 ppm (6.4 to 49.152 MHz) ✓ STRATUM 3
 ± 0.50 ppm (6.4 to 49.152 MHz)
 ± 1.00 ppm or ± 2.00 ppm (6.4 to 54 MHz)
- Temperature Ranges Available:
 0 to 85°C, 0 to 70°C, -40 to 85°C or
 -20 to 70°C Packages Available:
- T - Series: 5 x 7mm - 10 Pad
- TV - Series: 5 x 7mm - 4 Pad
- 3.3 Vdc Operation
- Output Logic: LVCMOS or Clipped Sinewave
- Fixed Frequency - TCXO
- Voltage Controlled - VCTCXO
- Low Jitter <0.50 ps RMS
- Low Phase Noise
- Tri-State Enable/Disable: (T Model Series Only)
- Tape and Reel Packaging
- RoHS Compliant / Lead Free ✓ RoHS

Applications:

- IEEE 1588 Applications
- Synchronous Ethernet slave clocks, ITU-T G.8262 EEC options 1 & 2
- Compliant to Stratum 3, GR-1244-CORE & GR-253-CORE
- Wireless Communications
- Small Cells
- Test and Measurement
- GPS

Standard Frequencies Available *

* 6.4, 9.72, 10, 10.24, 12.5, 12.8, 13.5, 19.2, 19.44, 20, 20.48, 25, 27, 38.88 MHz

Available frequencies from the factory for small quantity orders or quick delivery.

Additional frequencies are available. Alternate package outline for select part numbers 38MHz to 52MHz

** Not all

Models
available at
Digi-Key

Ordering Information

TV	5	0	4	- 010.0M
Type / Package TCXO / VCTCXO Series T = 5.0x7.0 mm 10 Pads TV = 5.0x7.0 mm 4 Pads	Temperature Range 3 = 0 to 85 °C 5 = 0 to 70 °C 6 = -40 to 85 °C 7 = -20 to 70 °C	Frequency Stability 0 = ± 0.28 ppm 1 = ± 0.50 ppm 2 = ± 1.00 ppm 3 = ± 2.00 ppm	Features 2 = TCXO, LVCMOS, 3.3 Vdc 3 = TCXO, Clipped Sinewave, 3.3 Vdc 4 = VCTCXO, LVCMOS, 3.3 Vdc 5 = VCTCXO, Clipped Sinewave, 3.3 Vdc	Output Frequency Frequency Format -xxx.xM Min -xxx.xxxxxM Max *Amount of numbers after the decimal point. M = MHz

Example: Part Number

TV504-010.0M = 5x7mm 4 pad package, ± 0.28 ppm, 0 to 70°C, 3.3 Vdc, LVCMOS Output, VCTCXO
 T715-012.8M = 5x7mm 10 pad package, ± 0.50 ppm, -20 to 70°C, 3.3 Vdc, Clipped Sinewave Output, VCTCXO
 T522-050.0M = 5x7mm 10 pad package, ± 1.0 ppm, 0 to 70°C, 3.3 Vdc, LVCMOS Output, TCXO
 TV602-010.0M = 5x7mm 4 pad package, ± 0.28 ppm, -40 to 85°C, 3.3 Vdc, LVCMOS Output, TCXO



Absolute Maximum Ratings

Parameter	Minimum	Nominal	Maximum	Units	Notes
Storage Temperature	-55	-	95	°C	
Supply Voltage (Vcc)	-0.5	-	6.0	Vdc	
Input Voltage	-0.5	-	Vcc + 0.5	Vdc	

Operating Specifications

Parameter		Minimum	Nominal	Maximum	Units	Notes
Output Frequency (Fo)						
Models Tx0x, TVx0x		6.4	-	49.152	MHz	
Models Tx1x, TVx1x		6.4	-	49.152	MHz	
Models Tx2x, TVx2x		6.4	-	54	MHz	
Models Tx3x, TVx3x		6.4	-	54	MHz	
Operating Temperature Range		(See Ordering Information for full part number)				
Models T3xx, TV3xx		0	-	85	°C	
Models T5xx, TV5xx		0	-	70	°C	
Models T6xx, TV6xx		-40	-	85	°C	
Models T7xx, TV7xx		-20	-	70	°C	
Frequency Calibration @ 25 °C	-1.0	-	1.0	ppm	1	
Frequency Stability (See Ordering Information for full part number)	Per STRATUM 3 GR-1244-CORE					
	Frequency Stability ±0.28 ppm is only available in the frequency range of 6.4 to 49.152 MHz.					
Models Tx0x, TVx0x		-0.28	-	0.28	ppm	2
Holdover Stability		-0.32	-	0.32	ppm	3
Constant Temperature Stability		-40	-	40	ppb	Over 24 Hrs.
Frequency Stability		(See Ordering Information for full part number)				
Models Tx1x, TVx1x		-0.50	-	0.50	ppm	2
Models Tx2x, TVx2x		-1.00	-	1.00	ppm	2
Models Tx3x, TVx3x		-2.00	-	2.00	ppm	2
Frequency vs. Load Stability		-0.05	-	0.05	ppm	±5%
Frequency vs. Voltage Stability		-0.05	-	0.05	ppm	±5%
Static Temperature Hysteresis		-	-	0.40	ppm	4
Freq. shift after reflow soldering		-1.0	-	1.0	ppm	5
Long Term Stability		-1.0	-	1.0	ppm	6
Aging						
per Life (20 Years)		-3.0	-	3.0	ppm	
per Day		-40	-	40	ppb	
Total Frequency Tolerance		-4.6	-	4.6	ppm	7
Supply Voltage (Vcc)		3.135	3.30	3.465	Vdc	
Supply Current (Icc) LVCMOS		-	2.1	6.0	mA	
Clipped Sinewave		-	1.3	2.9	mA	
Jitter:						
Period Jitter		-	3.0	5.0	ps RMS	
Integrated Phase Jitter (12K to Fo/2)		-	0.3	1.0	ps RMS	8
Allan Deviation (1s)		-	1.0E-10	-		
Typical SSB Phase Noise						
For Fo		10.0 MHz	25.0 MHz	50.0 MHz		
@ 10 Hz offset		-98	-90	-73	dBc/Hz	
@ 100 Hz offset		-125	-120	-103	dBc/Hz	
@ 1 KHz offset		-143	-140	-134	dBc/Hz	
@ 10 KHz offset		-151	-151	-151	dBc/Hz	
@ 100 KHz offset		-152	-152	-152	dBc/Hz	
@ 1 MHz offset		-155	-154	-154	dBc/Hz	
Start-Up Time		-	-	10	ms	

Control Voltage Input Characteristics

Parameter	Minimum	Nominal	Maximum	Units	Notes
Control Voltage	0.3	1.65	3.0	V	
Frequency Pullability	±10	±12	-	ppm	
Pull Slope (Vc=1.65V)	-	8.00	-	ppm/V	
Control Voltage Slope	Positive Slope				
Monotonic Linearity	-	-	5	%	
Input Impedance	100K	-	-	Ohm	
Modulation Bandwidth (3dB)	10	-	-		KHz

OE Enable /Disable Input Characteristics (Pad 8) T Series only

Parameter	Minimum	Nominal	Maximum	Units	Notes
Enable Input Voltage -(Vih)	70%Vcc	-	-	Vdc	9
Disable Input Voltage - (Vil)	-	-	30%Vcc	Vdc	9
Function	Output				
Low:	Disabled (High Impedance)				
High or Open:	Enabled				

LVC MOS Output Characteristics

Parameter	Minimum	Nominal	Maximum	Units	Notes
Load (CL)	-	15	-	pF	10
Voltage (High) (Voh)	90%Vcc	-	-	Vdc	
(Low) (Vol)	-	-	10%Vcc	Vdc	
Current (High) (Ioh)	-4	-	-	mA	
(Low) (Iol)	-	-	4	mA	
Duty Cycle at 50% of Vcc	45	50	55	%	
Rise / Fall Time 10% to 90%	-	4	8	ns	

Clipped Sinewave Output Characteristics

Parameter	Minimum	Nominal	Maximum	Units	Notes
Load (RC)					11
Output Load Resistance	-	10K	-	Ohm	12
Output Load Capacitance	-	10	-	pF	
Output Voltage (< 40 MHz)	1.0	1.2	-	V	pk-pk
Output Voltage (≥40 MHz)	0.8	1.0	-	V	pk-pk
Output Impedance	-	200	-	Ohms	

Package Characteristics

Package	Hermetically sealed ceramic package with grounded metal cover
---------	---

Environmental Characteristics


Vibration:	Vibration per Mil Std 883E Method 2007.3 Test Condition A.
Shock:	Mechanical Shock per Mil Std 883E Method 2002.4 Test Condition B.
Soldering Process:	RoHS compliant lead free. See soldering profile on page 6.

Notes:


1. Initial calibration @ 25°C. ±2°C, for VCTCXO's Vc = 1.65V. Specifications at time of shipment
2. Frequency stability vs. change in temperature. $[\pm(F_{max}-F_{min})/(2 \cdot F_0)]$. For VCTCXO's - Vc = 1.65V
3. Inclusive of frequency stability, supply voltage change (±1%), aging, for 24 hours. Per STRATUM 3 GR-1244-CORE.
4. Frequency change after reciprocal temperature ramped over the operating range. Frequency measured before and after at 25°C
5. Two consecutive solder reflows after 1 hour recovery @ 25°C.
6. Frequency drift over 1 year @ 25°C.
7. Inclusive of calibration @ 25°C, frequency vs. change in temperature, change in supply voltage (±5%), load change (±5%), reflow soldering process and 20 years aging.
8. BW = 12 KHz to 20 MHz
9. Leave Pad 8 on the T Series unconnected if enable / disable function is not required. When tri-stated, the output stage is disabled but the oscillator and compensation circuit are still active (current consumption < 1 mA).
10. Attention: To achieve optimal frequency stability, and in some cases to meet the specification stated on this data sheet, it is required that the circuit connected to this TCXO output must have the equivalent input capacitance that is specified by the nominal load capacitance. Deviations from the nominal load capacitance will have a graduated effect on the stability of approximately 20 ppb per pF load difference.
11. Load components are required for proper operation of the device.
12. Output is AC coupled.

Bulletin	Tx176
Page	3 of 6
Revision	19
Date	01 April 2015

T Series Package Outline



T Series Suggested Pad Layout





* Do not route any traces in the keep out area. It is recommended the next layer under the keep out area is to be ground plane.

T Series Pad Connections


- 1: Do Not Connect
- 2: Do Not Connect
- 3: Do Not Connect
- 4: Ground
- 5: Output
- 6: Do Not Connect
- 7: Do Not Connect
- 8: Enable / Disable (OE)
- 9: Supply Voltage (Vcc)
- 10: VCTCXO: Control Voltage (Vc)
TCXO: N/C

T Series Alternate Package Outline




Alternate package applies to select part numbers in the 38 to 52MHz frequency range. The differences are the top view crystal size, and the overall height. Bottom view, suggested pad layout, and pad connections all remain the same as above.

TV Series Package Outline



TV Series Suggested Pad Layout





* Do not route any traces in the keep out area. It is recommended the next layer under the keep out area is to be ground plane.

TV Series Pad Connections


- 1: VCTCXO: Voltage Control (Vc)
TCXO: N/C
- 2: Ground
- 3: Output
- 4: Supply (Vcc)

T Series Design Recommendations


TV Series Design Recommendations




T Series LVCMOS Test Circuit




TV Series LVCMOS Test Circuit




LVCMOS Output Waveform




T Series Clipped Sinewave Test Circuit



TV Series Clipped Sinewave Test Circuit




Clipped Sinewave Output Waveform




Note: The clipped sinewave output is AC coupled


Phase Noise Information




TIE




MTIE




TDEV



5x7mm Tape and Reel Information



Solder Profile



Meets IPC/JEDEC J-STD-020C

Revision History

Revision	Date	Action
17	02/11/14	Updated specifications and combined the T and TV series data sheets.
18	09/15/14	Added Alternate Package Outline

Bulletin	Tx176
Page	6 of 6
Revision	19
Date	01 April 2015