

Metal Film Resistors, Industrial, $\pm 2\%$ and $\pm 5\%$ Tolerance

FEATURES

- Dual power rating:
 $P_{70} = 0.25\text{ W}$ with 1.5 % stability
 $P_{70} = 0.50\text{ W}$ with 2.0 % stability
- $\pm 2\%$ and $\pm 5\%$ tolerance
- Temperature coefficient: $\pm 100\text{ ppm/K}$ and $\pm 200\text{ ppm/K}$
- Tape and reel packaging for automatic insertion (52.4 mm inside tape spacing per EIA-296-E)
- Flame retardant epoxy conformal coating (red brown color)
- Standard 4 band color code marking for ease of identification after mounting
- Pure tin plating provides compatibility with lead (Pb)-free and lead containing soldering processes
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


RoHS
COMPLIANT


STANDARD ELECTRICAL SPECIFICATIONS

PRODUCT	POWER RATING P_{70} W	LIMITING ELEMENT VOLTAGE MAX. V_{E}	TEMPERATURE COEFFICIENT $\pm\text{ ppm/K}$	TOLERANCE $\pm\%$	RESISTANCE RANGE Ω	E-SERIES
CCF07	0.25	250	100	2, 5	10 to 1M	E24
CCF07	0.5	250	100	2, 5	10 to 1M	E24
CCF07	0.25	250	200	5	1.1M to 2M	E24
CCF07	0.5	250	200	5	1.1M to 2M	E24


TECHNICAL SPECIFICATIONS

PARAMETER	UNIT	CCF07
Rated Dissipation, P_{70}	W	0.25/0.5
Maximum Working Voltage, U_{max}	V $_{\text{E}}$	≤ 250
Insulation Voltage (1 min)	V $_{\text{eff}}$	500
Dielectric Strength	V $_{\text{AC}}$	450
Insulation Resistance	Ω	$\geq 10^{11}$
Operating Temperature Range	$^{\circ}\text{C}$	-65 to +150
Terminal Strength (pull test)	lb	2
Weight	g	0.35 max.


PART NUMBER AND PRODUCT DESCRIPTION

PART NUMBER: CCF07240RGKE36

C	C	F	0	7	2	4	0	R	G	K	E	3	6			
PRODUCT	RESISTANCE VALUE		TOLERANCE CODE		TEMPERATURE COEFFICIENT		PACKAGING		SPECIAL							
CCF07	R = decimal K = thousand M = million 10R0 = 10 Ω 680K = 680 kΩ 2M00 = 2.0 MΩ		G = ± 2 % J = ± 5 %		K = 100 ppm/K N = 200 ppm/K		E36 = lead (Pb)-free T/R (5000 pieces)		Blank = standard (dash number) (up to 3 digits) From 1 to 999 as applicable							

DIMENSIONS in inches (millimeters)


PRODUCT	A	B	C (Max.)	D	E
CCF07	0.245 ± 0.020 (6.22 $\pm$ 0.51)	0.090 ± 0.008 (2.29 $\pm$ 0.20)	0.295 (7.5)	0.022 ± 0.002 (0.58 $\pm$ 0.05)	1.100 ± 0.040 (27.94 $\pm$ 1.02)

DERATING

MARKING

The nominal resistance and tolerance are marked on the resistor using four colored bands in accordance with IEC 60062, marking codes for resistors and capacitors.

RESISTANCE VALUES

Vishay CCF07 is available in the standard 24 resistance values per decade. Values are obtained from the following decade table by multiplying by powers of 10. As an example: 24 can represent 24 Ω , 240 Ω , 2.4 k Ω , 24 k Ω or 240 k Ω .

10	18	33	56
11	20	36	62
12	22	39	68
13	24	43	75
15	27	47	82
16	30	51	91

PERFORMANCE

TEST ⁽¹⁾	MAX. ΔR (Typical Test Lots)
Thermal Shock	± 1.0 %
Short Time Overload	± 0.5 %
Low Temperature Operation	± 0.5 %
Moisture Resistance	± 1.5 %
Resistance to Soldering Heat	± 0.5 %
Shock/Bump	± 0.5 %
Vibration	± 0.5 %
Terminal Strength	± 0.5 %
Dielectric Withstanding Voltage	± 0.5 %
Life	± 1.5 % ⁽²⁾

Notes

⁽¹⁾ Test specifications as per IEC 60115-1

⁽²⁾ Life ΔR is ± 2.0 % for 1/2 W rating



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Vishay:

[CCF071K50JNR36](#) [CCF078K20GKR36](#) [CCF07220RGKR36](#) [CCF076K80JKR36](#) [CCF07200RGKR36](#)
[CCF07430KGKR36](#) [CCF07270KGKR36](#) [CCF07270RGKR36](#) [CCF072K40GKR36](#) [CCF072K20GKR36](#)
[CCF0747R0JNR36](#) [CCF0768R0JKR36](#) [CCF0710R0JKR36](#) [CCF0775R0JKR36](#) [CCF0727R0JKR36](#)
[CCF0722R0JKR36](#) [CCF0720R0JKR36](#) [CCF0739R0JKR36](#) [CCF0751R0JKR36](#) [CCF07330KJKR36](#)
[CCF07470RGKR36](#) [CCF071K60JKR36](#) [CCF07620RGKR36](#) [CCF071K80JNR36](#) [CCF07680RGKR36](#)
[CCF07510RGKR36](#) [CCF073K00JKR36](#) [CCF071M00JKR36](#) [CCF07560RGKR36](#) [CCF07300RGKR36](#)
[CCF07240KGKR36](#) [CCF07390RGKR36](#) [CCF07330RGKR36](#) [CCF075K10JKR36](#) [CCF077K50GKR36](#)
[CCF0715K0GKR36](#) [CCF07200KGKR36](#) [CCF075K10GKR36](#) [CCF075K60GKR36](#) [CCF0718K0GKR36](#)
[CCF0711K0GKR36](#) [CCF0710K0GKR36](#) [CCF071K00GKR36](#) [CCF071M00GKR36](#) [CCF072K40JKR36](#)
[CCF074K70GKR36](#) [CCF073K00GKR36](#) [CCF072K20JKR36](#) [CCF072K00GKR36](#) [CCF0733R0GKR36](#)
[CCF0713R0GKR36](#) [CCF0718R0GKR36](#) [CCF0756R0GKR36](#) [CCF0710R0GKR36](#) [CCF0775R0GKR36](#)
[CCF0756K0GKR36](#) [CCF0751K0JKR36](#) [CCF07330KGKR36](#) [CCF07110KGKR36](#) [CCF071K00JNR36](#)
[CCF072K00JKR36](#) [CCF07910RGKR36](#) [CCF0743K0GKR36](#) [CCF074K70GKR36](#) [CCF074K40GKR36](#)
[CCF07120RGKR36](#) [CCF07390RJKR36](#) [CCF076K20GKR36](#) [CCF076K80GKR36](#) [CCF0733K0GKR36](#)
[CCF07270KJKR36](#) [CCF0730K0GKR36](#) [CCF0712K0GKR36](#) [CCF07100KJKR36](#) [CCF0720K0GKR36](#)
[CCF0722K0GKR36](#) [CCF0718K5%TR](#) [CCF07625%TR](#) [CCF07 180K 5%TR](#) [CCF07100KJKE36](#) [CCF0710R0JKE36](#)
[CCF07180KJNR36](#) [CCF071M50JKR36](#) [CCF0720R0GKE36](#) [CCF0720R0JKE36](#) [CCF07220RJKE36](#)
[CCF07240RJKE36](#) [CCF0727K0GKE36](#) [CCF072K20JKE36](#) [CCF072K40JKE36](#) [CCF07330KJKE36](#)
[CCF073K30JKE36](#) [CCF07470KGKE36](#) [CCF07470KJKE36](#) [CCF07470RJKE36](#) [CCF0747K0JKE36](#)
[CCF0751K0JKE36](#) [CCF075K10JKE36](#) [CCF075K60JKE36](#) [CCF07620RGKE36](#)