SuperServer 6017R-N3RFT+

Integrated Board

Super X9DRW-3TF+

Available Colors: Black

▸ Drivers & Utilities ▸ BIOS ▸ IPMI ▸ Tested Memory ▸ Tested HDD
▸ Manuals ▸ OS Certification Matrix ▸ Quick-References

Key Features

1. Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and **E5-2600 v2** family†
2. Up to 1.5TB ECC DDR3, up to 1866MHz; 24x DIMM sockets
3. 1 PCI-E 3.0 (x8) Low-profile, 1 PCI-E 3.0 (x16) & 1 PCI-E 3.0 (x8) Full-height slots (see below for details)
4. Intel i350 Dual port GbE & Intel X540 Dual port 10GBase-T Controllers
5. 4x 3.5" Hot-swap SAS/SATA HDD Bays Connected to onboard storage controller
6. 750/700W Redundant Power Supplies **Gold Level Certified**

Note: Image above may show a varied configuration or optional parts. Please refer to parts list for standard parts included.

Specifications

Product SKUs	
SYS-6017R-N3RFT+	▪ SuperServer 6017R-N3RFT+ (**Black**)

Motherboard	
Super X9DRW-3TF+	

Processor/Cache	
CPU	▪ Dual Socket R (LGA 2011) ▪ Intel® Xeon® processor E5-2600 and **E5-2600 v2** family† (up to 130W TDP)
Note	† BIOS version 3.0 or above is required
Cache	▪ Up to 30MB
System Bus	▪ QPI up to 8 GT/s

System Memory	
Memory Capacity	▪ 24x 240-pin DDR3 DIMM sockets ▪ Up to 1.5TB DDR3 ECC LRDIMM ▪ Up to 768GB DDR3 ECC Registered memory (RDIMM) ▪ Up to 128GB DDR3 ECC Un-Buffered memory (UDIMM)
Memory Type	▪ 1866/1600/1333/1066/800MHz ECC DDR3 SDRAM 72-bit, 240-pin gold-plated DIMMs
DIMM Sizes	▪ 32GB, 16GB, 8GB, 4GB, 2GB, 1GB
Memory Voltage	▪ 1.5 V, 1.35 V
Error Detection	▪ Corrects single-bit errors ▪ Detects double-bit errors (using ECC memory)

On-Board Devices	
Chipset	▪ Intel® C606 Chipset
SAS	▪ SAS from C606 ▪ RAID 0, 1, 10 support
SATA	▪ Via Cable for SATA controller ▪ SATA 2.0 3Gbps with RAID 0, 1, 5, 10 ▪ SATA 3.0 6Gbps with RAID 0, 1
IPMI	▪ Support for Intelligent Platform Management Interface v.2.0 ▪ IPMI 2.0 with virtual media over LAN and KVM-over-LAN support ▪ Nuvoton WPCM450 BMC
Network Controllers	▪ Intel® X540 Dual Port 10GBase-T ▪ Intel® i350 Dual Port Gigabit Ethernet ▪ Virtual Machine Device Queues reduce I/O overhead ▪ Supports 10GBase-T, 100BASE-TX, and 1000BASE-T, RJ45 output ▪ 1x Realtek RTL8201N PHY (dedicated IPMI)
Graphics	▪ Matrox G200eW

Input / Output	
SAS	▪ 4x SAS ports (3Gbps)
LAN	▪ 2x RJ45 10GBase-T ports ▪ 2x RJ45 Gigabit Ethernet LAN ports ▪ 1x RJ45 Dedicated IPMI LAN port
USB	▪ 7x USB 2.0 ports total (2x rear + 4x via header + 1x Type A)
VGA	▪ 1x VGA port
Serial Port / Header	▪ 1x Fast UART 16550 port / 1 Header

Chassis	
Form Factor	▪ 1U Rackmount
Model	▪ CSE-819TQ-R700WB

Dimensions	
Width	▪ 17.2" (437mm)
Height	▪ 1.7" (43mm)
Depth	▪ 27.75" (705mm)
Gross Weight	▪ 43 lbs (19.45kg)
Available Colors	▪ Black

Front Panel	
Buttons	▪ Power On/Off button ▪ System Reset button ▪ UID button
LEDs	▪ Power status LED ▪ HDD activity LED ▪ 2x Network activity LEDs ▪ Universal Information (UID) LED

Expansion Slots	
PCI-Express	▪ 1 PCI-E 3.0 (x16) Full-height (10" length) ▪ 1 PCI-E 3.0 (x8) Full-height (6.6" length) ▪ 1 PCI-E 3.0 (x8) Low-profile (4.1" length) ▪ UIO AOC Compatibility Matrix (Both CPUs need to be installed for full access to PCI-E slots and onboard controllers. See manual block diagram and AOC Support for details.)

Drive Bays	
Hot-swap	▪ 4x 3.5" Hot-swap SAS / SATA HDD trays (connected to onboard storage - 4 SAS ports)

Peripheral Drives	
DVD-ROM	▪ Slim DVD-ROM drive (optional)

Backplane
1x 1U SAS2 / SATA backplane

System Cooling	
Fans	▪ 6x 4cm Counter-rotating PWM fans

Power Supply	
700W/750W Redundant AC-DC high-efficiency power supply with PMBus and I2C	
AC Input	▪ 700W: 100-140 V, 50-60 Hz, 8.5-6 Amp ▪ 750W: 180-240 V, 60-50 Hz, 5-3.8 Amp
DC Output +5V standby	▪ 3 Amp
DC Output +12V	▪ 700W: 58 Amp @ 100-140V ▪ 750W: 62 Amp @ 180-240V
With Power Distributor	▪ +5V: 25 Amp ▪ +3.3V: 25 Amp ▪ -12V: 0.6 Amp
Certification	80 PLUS GOLD Gold Certified

System BIOS	
BIOS Type	▪ 128Mb SPI Flash EEPROM with AMI BIOS
BIOS Features	▪ Plug and Play (PnP) ▪ APM 1.2 ▪ PCI 2.2 ▪ ACPI 1.0 / 2.0 ▪ USB Keyboard support ▪ SMBIOS 2.3 ▪ UEFI

Operating Environment / Compliance	
RoHS	▪ RoHS Compliant
Environmental Spec.	▪ Operating Temperature: 5°C to 35°C (41°F to 95°F) ▪ Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) ▪ Operating Relative Humidity: 8% to 90% (non-condensing) ▪ Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List

See Parts List

Copyright © 2015 Super Micro Computer, Inc.
Information in this document is subject to change without notice.
Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.