

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.





PANDUIT	WIRE RANGE COPPER	CURRENT RATING (AMPS)	STUD SIZE IN	DIMENSIONS - IN [mm] +/02 [.5]						HEX
PART NUMBER				Α	W	G	S	С	Т	SIZE*
CD35-36SL-QY	#14 - #6 (1) #10 & (1) #12 (1) #12 & (1) #14 (2) #10 (2) #12 (2) #14	50	3/16	2.13 [54.1]	.38 [9.7]	.22 [5.6]	1.00 [25.4]	.38 [9.7]	.07 [1.8]	SLOTTED
CD70-14SL-QY	#8 - #2	90	1/4	2.26 [57.4]	.50 [12.7]	.25 [6.4]	1.00 [25.4]	.38 [9.7]	.08 [2.0]	SLOTTED
CD125-14SL-QY	#2 - #1/0	125	1/4	2.94 [74.7]	.62 [15.7]	.44 [11.2]	1.00 [25.4]	.44 [11.2]	.11 [2.8]	SLOTTED
CD225-56HKR-Q	#2 - #4/0	225	5/16	3.38 [85.9]	.99 [25.1]	.50 [12.7]	1.00 [25.4]	.63 [16.0]	.12 [3.0]	7/32
CD300-38HK-3Y	#1 - 350	300	3/8	4.94 [125.5]	.99 [25.1]	.94 [23.9]	1.00 [25.4]	1.38 [35.1]	.12 [3.0]	5/16
CD400-38HK-3Y	#1/0 - 500	400	3/8	5.62 [142.7]	1.50 [38.1]	.94 [23.9]	1.75 [44.5]	.88 [22.4]	.18 [4.6]	5/16
CD650-12HK-3Y	600 - 1000	650	1/2	6.88 [174.8]		1.19 [30.2]	1.75 [44.5]	1.75 [44.5]	.25 [6.4]	3/8

^{*}HEX STYLE & SIZE MAY DIFFER FROM CHART. DIFFERENCE IN SIZE WILL NOT AFFECT FIT, FORM, OR FUNCTION OF PART

NOTES:

- 1. MATERIAL: BODY - COPPER SCREW - STEEL, ZINC PLATED
- 2. cULus LISTEDFOR USE UP TO 600V & TEMPERATURE RATED 90°C
- 3. RATED FOR USE WITH COPPER STRANDED CODE CONDUCTOR ONLY
- 4. THESE PARTS ARE ROHS COMPLIANT
- 5. SEE PACKAGING LABEL FOR TIGHTENING TORQUE INFORMATION
- 6. PKG QTY: Q = 25 3 = 3



								PANDUIT CORP.	TINLEY PARK, ILLINOIS
04	8/16	JHNU	JHNU	ADDED CD225-56HKR-Q, REMOVED CD225-56HKR-QY	N41666BA-C41666	RGB	RGB	CD SERIES COPPER MECHANIC	CAL CONNECTORS
03	4/13	JHNU	JHNU	REVISED WIRE RANGE FOR CD225-56HK-QY: 2-4/0 WAS 6-4/0 REVISED WIRE RANGE FOR CD70-14SL-QY: 8-2 WAS 12-2	N41666BA-C41666	RGB	RGB	CUSTOMER DRAV	VING
02	2/12	JHNU	JHNU	REVISED "W" DIMENSION: CD35 WAS .37, CD70 WAS .47, CD650 WAS 1.97 REVISED "T" DIMENSION: CD650 WAS .22 REVISED PART NUMBERS: ADDED "SL" SUFFIX TO CD35, CD70, CD125 ADDED "HK" SUFFIX TO CD225, CD300, CD400, CD650	N41666BA-C41666	RGB	RGB	UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCES ARE: (.X) ± (.XXX) ± (.XX) ± ANGLES ±	UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION
01	1/07	JHNU	JHNU	ADDED PART WEIGHT COLUMN TO TABLE	PC00640			DRAWN BY JHNU MAT'L:	SCALE NONE
00	3/06	JHNU	LEM	DRAWING RELEASED - ROHS COMPLIANT	PC00348			DATE	DRAWING NO / CAD FILE DWG
REV	DATE	BY	СНК	DESCRIPTION	ECN	-R	SUP	СНК'D	C41666_03 B