samtec



(2.00 mm) .0787"

ESQT SERIES

FLEXIBLE ELEVATED SOCKET STRIPS

SPECIFICATIONS

For complete specifications see www.samtec.com?ESQT

Insulator Material:
Black Liquid Crystal Polymer
Contact Material:
Phosphor Bronze
Plating:
Sn or Au over
50 µ" (1.27 µm) Ni
Current Rating (ESQT/TMMH):
4.5 A per pin
(2 pins powered)
Operating Temp Range:
-55 °C to +125 °C
Insertion Depth:
(2.62 mm) .103" to
(5.03 mm) .198" with
(0.38 mm) .015" wipe
Max Cycles:
100 with 10 µ" (0.25 µm) Au
RoHS Compliant:
Yes
Lead–Free Solderable:
Yes, for -S, -D & -Q
(Wave only for -T, -5 & -6)

Board Mates:
TMMH, TMM, MTMM, MMT, TW, LTMM, ZLTMM, ESQT, PTT, TSH, TMMS

Cable Mates:
TCMD



TIGER BUY™ CONTACT

APPLICATION SPECIFIC OPTION:
NOTEBOOK 2.5" DISK DRIVE INTERFACE

Call for part number.

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality

FILE NO. E111594

Note:
This Series is non-standard, non-returnable.

ESQT	1	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	ROW OPTION	BODY HEIGHT	OTHER OPTION
		02 thru 50	Specify LEAD STYLE from chart	–F = Gold flash on contact, Matte Tin on tail –L = 10 µ" (0.25 µm) Gold on contact, Matte Tin on tail –M = 20 µ" (0.51 µm) Gold on contact, Matte Tin on tail –GF = 15 µ" (0.38 µm) Gold on contact, Gold flash on tail (Recommended for self-nesting) (–02 lead style only)	–S = Single Row –D = Double Row –T = Triple Row –Q = Quad Row –5 = Five Row –6 = Six Row	–"XXX" = Body Height (in inches) (7.87 mm) .310" minimum for –S, –D, –Q (9.53 mm) .375" minimum for –T, –5, –6	–"XXX" = Polarized Position (Indicate position number)





LEAD STYLE	A	MAX TAIL	MAX BODY HEIGHT
–02	(21.59) .850	(13.72) .540	(20.32) .800
–03	(11.63) .458	(3.76) .148	(10.36) .408

OTHER SOLUTIONS



Paste In Hole (PIH) processing. Contact Samtec ASP Group.
(Not recommended for stack through applications)

Other Solutions

Surface Mount
See SQW and TLE Series.



Low Profile
See CLT Series.



High Reliability
See SMM Series.



Right-Angle
See SQW Series.



PC/104-Plus™ Sockets
See ESQT-368 and PTHF Series.



Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications.
Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.