

## Control cabinet feed-through - CUC-BH-M12D1PBK-S/R4BE - 1414398

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Control cabinet feed-through, M12, 4-pos., D-coded to RJ45 socket, socket entry: 180°, IP65/IP67

### Why buy this product

- Compact design
- 100 Mbps
- IP65/67
- UL



**Ethernet**

### Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	40.0 g
Custom tariff number	85366990
Country of origin	Germany

### Technical data

#### Mechanical characteristics

Shielded	yes
Insertion/withdrawal cycles	≥ 100
Cable exit	straight
Color	black
Mounting type	Rear mounting

#### Ambient conditions

Ambient temperature (operation)	-25 °C ... 85 °C
---------------------------------	------------------

#### Material data

Control cabinet feed-through - CUC-BH-M12D1PBK-S/R4BE - 1414398

Technical data

Material data

Flammability rating according to UL 94	V0
Housing material	PA
Contact material	Copper alloy

Electrical characteristics

Nominal voltage $U_N$	60 V
Nominal current $I_N$	0.5 A
Transmission characteristics (category)	CAT5 (IEC 11801:2002)
GRP transmission properties	Ethernet
Transmission speed	100 Mbps
Rated current	1.75 A

Standards and Regulations


Flammability rating according to UL 94	V0
--	----

Drawings

Explosion  
drawing


Exploded  
drawing

Dimensional drawing




Panel cutout

Dimensional drawing



Circuit diagram



Panel cutout

Circuit diagram

## Control cabinet feed-through - CUC-BH-M12D1PBK-S/R4BE - 1414398

### Classifications

eCl@ss

eCl@ss 8.0	27141134
eCl@ss 9.0	27141134

ETIM

ETIM 5.0	EC001283
----------	----------

### Approvals

Approvals

Approvals


EAC / UL Listed / cUL Listed / EAC / cULus Listed


Ex Approvals

Approvals submitted

### Approval details

EAC
-----

UL Listed 	
Nominal current I <sub>N</sub>	0.5 A
Nominal voltage U <sub>N</sub>	60 V

cUL Listed 	
Nominal current I <sub>N</sub>	0.5 A
Nominal voltage U <sub>N</sub>	60 V

## Control cabinet feed-through - CUC-BH-M12D1PBK-S/R4BE - 1414398

### Approvals

EAC

cULus Listed 