



# NOTES:

1. TERMINAL TO BE USED IN HOUSING 70066-\*\*\*\* AND 70450-\*\*\*\*.
2. REFER TO PRODUCT SPECIFICATION PS-70058.
3. REFER TO MOLEX OPERATIONS AND SERVICE MANUAL FOR CRIMP DETAILS.
4. TERMINAL TO BE USED WITH (0.64)/.025 SQUARE PINS.
5. TERMINAL TO BE USED WITH 24-30 AWG STRANDED WIRE WITH (1.52)/.060 MAXIMUM DIAMETER INSULATION.
6. TERMINALS SUPPLIED IN REEL FORM.
7. CRIMP SIZE INDICATOR A=24-30 AWG

# PLATING:

.000030 MINIMUM GOLD PLATE IN SELECT AREA,  
.000075 MINIMUM TIN PLATE IN SELECT AREA,  
OVER NICKEL PLATE OVERALL.

REEL UNWIND DIR EC NO: UCP2013-5345 DRAWN:RWHIPPLE 2013/06/11 CHKD:DMORGAN 2013/06/11 APPR:SMILLER 2013/07/09	DESCRIPTION	QUALITY SYMBOLS <div>▽=0</div> <div>▽=0</div> <div>▽=0</div>	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE 10:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION			
				mm	INCH	DRAWN BY RWHIPPLE	DATE 2013/06/11	TITLE TERMONAL - BOX/CRIMP FOR 24-30 AWG ON A REEL				
			4 PLACES	± ---	± ---	CHECKED BY JAS	DATE 1988/03/02					
			3 PLACES	± ---	± .005	APPROVED BY SMILLER 2013/07/09		DOCUMENT NO. SD-70058-0008				
			2 PLACES	± 0.13	± .01							
1 PLACE	± 0.25	± ---	SHEET NO. 1 OF 1									
0 PLACE	± ---	± ---										
ANGULAR ±1/2°								MATERIAL NO. 16-02-0083				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			SIZE B		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION							

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION