



ALUMINUM ELECTROLYTIC CAPACITORS

nichicon

WT series Chip Type, Wide Temperature Range





- Chip type operating over wide temperature range of to -55 to $+105^{\circ}\text{C}$.
- Designed for surface mounting on high density PC board.
- Applicable to automatic mounting machine fed with carrier tape.
- Compliant to the RoHS directive (2011/65/EU).



Specifications


Item	Performance Characteristics								
Category Temperature Range	-55 to +105°C								
Rated Voltage Range	4 to 50V								
Rated Capacitance Range	0.1 to 1500μF								
Capacitance Tolerance	±20% at 120Hz, 20°C								
Leakage Current	After 2 minutes' application of rated voltage, leakage current is not more than 0.01CV or 3 (μA) , whichever is greater.								
Tangent of loss angle (tan δ)	Measurement frequency : 120Hz at 20°C								
	Rated voltage (V)	4	6.3	10	16	25	35	50	
	tan δ (MAX.)	0.40	0.30	0.24	0.20	0.16	0.14	0.14	
Stability at Low Temperature	Measurement frequency : 120Hz								
	Rated voltage (V)		4	6.3	10	16	25	35	50
	Impedance ratio	Z-25°C / Z+20°C	7	4	3	2	2	2	2
	ZT / Z20 (MAX.)	Z-40°C / Z+20°C	15	8	8	4	4	3	3
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 1000 hours at 105°C.				Capacitance change	Within ±25% of the initial capacitance value for capacitors of φ3mm unit, and 16V or less. Within ±20% of the initial capacitance value for capacitors of 25V or more.			
					tan δ	200% or less than the initial specified value			
					Leakage current	Less than or equal to the initial specified value			
Shelf Life	After storing the capacitors under no load at 105°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the specified values for the endurance characteristics listed above.								
Resistance to soldering heat	The capacitors are kept on a hot plate for 30 seconds, which is maintained at 250°C. The capacitors shall meet the characteristic requirements listed at right when they are removed from the plate and restored to 20°C.				Capacitance change	Within ±10% of the initial capacitance value			
					tan δ	Less than or equal to the initial specified value			
					Leakage current	Less than or equal to the initial specified value			
Marking	Black print on the case top.								

Chip Type



- ※1. Voltage mark for 6.3V is 「6V」. In case of marking for $\phi 3$ units, 「V」 for rated voltage is omitted.
 ※2. In case of marking for $\phi 3$ units. Lot No is expressed by a digit (month code).

Type numbering system (Example : 16V 10 μF)



$\phi D \times L$	3 × 5.4	4 × 5.4	5 × 5.4	6.3 × 5.4	6.3 × 5.8	6.3 × 7.7	8 × 5.4	8 × 10	10 × 10
A	1.5	1.8	2.1	2.4	2.4	2.4	3.3	2.9	3.2
B	3.3	4.3	5.3	6.6	6.6	6.6	8.3	8.3	10.3
C	3.3	4.3	5.3	6.6	6.6	6.6	8.3	8.3	10.3
E	0.8	1.0	1.3	2.2	2.2	2.2	2.3	3.1	4.5
L	5.4	5.4	5.4	5.4	5.8	7.7	5.4	10	10
H	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.8 to 1.1	0.8 to 1.1

● Dimension table in next page.

CAT.8100D

■ Dimensions

V	4	6.3	10	16	25	35	50		
Cap. (μF)	0G	0J	1A	1C	1E	1V	1H		
0.1	0R1						4 × 5.4 (3)	1.0	
0.22	R22						4 × 5.4 (3)	2.6	
0.33	R33						4 × 5.4 (3)	3.2	
0.47	R47						4 × 5.4 (3)	3.8	
1	010						4 × 5.4 (3)	6.3 (5.9)	
2.2	2R2					3 × 5.4	7.5	4 × 5.4 (3)	11 (9)
3.3	3R3					3 × 5.4	9	4 × 5.4	14
4.7	4R7					4 × 5.4 (3)	13 (10)	4 × 5.4	15
10	100				4 × 5.4 (3)	18 (14)	5 × 5.4	23	5 × 5.4
22	220	4 × 5.4	22	4 × 5.4	22	5 × 5.4	27	5 × 5.4	30
33	330	5 × 5.4	30	5 × 5.4	30	5 × 5.4	35	6.3 × 5.4	40
47	470	5 × 5.4	36	5 × 5.4	36	6.3 × 5.4	46	6.3 × 5.4	50
100	101	6.3 × 5.4	60	6.3 × 5.4	60	6.3 × 5.4	60	6.3 × 5.4	60
150	151	6.3 × 5.8	86	6.3 × 5.8	86	6.3 × 5.8	86	6.3 × 7.7	95
220	221	• 8 × 5.4	102 (91)	• 8 × 5.4	102 (91)	6.3 × 7.7	105	6.3 × 7.7	105
330	331	6.3 × 7.7	105	6.3 × 7.7	105	8 × 10	195	8 × 10	195
470	471	8 × 10	210	8 × 10	210	8 × 10	210	8 × 10	230
680	681	8 × 10	210	8 × 10	210	10 × 10	310	10 × 10	310
1000	102	8 × 10	230	8 × 10	230	10 × 10	310		
1500	152	10 × 10	310	10 × 10	310				

() is also available with φ3mm upon request. In such a case, [2] will be put at 12th digit of type numbering system.

Size φ6.3 × 5.8 is available for capacitors marked. " • " In such a case, [6] will be put at 12th digit of type numbering system.

Rated ripple current (mA rms) at 105°C 120Hz

● Frequency coefficient of rated ripple current

Frequency	50 Hz	120 Hz	300 Hz	1 kHz	10 kHz or more
Coefficient	0.70	1.00	1.17	1.36	1.50

- Taping specifications are given in page 23.
- Recommended land size, soldering by reflow are given in page 18, 19.
- Please select UX(p.154), UJ(p.160) series if high C/V products are required.
- Please refer to page 3 for the minimum order quantity.