



# SAW Components

Data Sheet B3802







**SAW Components**

**B3802**

**Low-Loss Filter**

**110,0 MHz**

**Data Sheet**

**Characteristics**

Operating temperature:  $T = 25\text{ }^{\circ}\text{C}$   
 Terminating source impedance:  $Z_S = 50\ \Omega$  and matching network  
 Terminating load impedance:  $Z_L = 50\ \Omega$  and matching network

		<b>min.</b>	<b>typ.</b>	<b>max.</b>	
<b>Center frequency</b>	$f_C$	109,9	110,0	110,1	MHz
<b>Minimum insertion attenuation</b>	$\alpha_{\min}$	—	6,8	10,0	dB
<b>Pass bandwidth</b>	$\alpha_{\text{rel}} \leq 3,0\text{ dB}$	$B_{3\text{dB}}$	3,75	4,0	—
	$\alpha_{\text{rel}} \leq 1,0\text{ dB}$	$B_{1\text{dB}}$	—	3,1	—
<b>Amplitude ripple</b> (max peak to adjacent valley)	$\Delta\alpha$				
	$f_C \pm 1,6\text{ MHz}$	—	0,5	—	dB
<b>Group delay ripple</b>	$\Delta\tau$				
	$f_C \pm 1,6\text{ MHz}$	—	45	80	ns
<b>Relative attenuation</b> (relative to $\alpha_{\min}$ )	$\alpha_{\text{rel}}$				
	60,0 MHz ... 100,0 MHz	40	42	—	dB
	100,0 MHz ... 105,5 MHz	36	41	—	dB
	114,5 MHz ... 120,0 MHz	36	41	—	dB
	120,0 MHz ... 160,0 MHz	38	43	—	dB
<b>Temperature coefficient of frequency</b>	$TC_f$	—	-18	—	ppm/K



**SAW Components**

**B3802**

**Low-Loss Filter**

**110,0 MHz**

**Data Sheet**

**Characteristics**


Operating temperature:  $T = -10 \dots 70 \text{ }^\circ\text{C}$   
 Terminating source impedance:  $Z_S = 50 \text{ } \Omega$  and matching network  
 Terminating load impedance:  $Z_L = 50 \text{ } \Omega$  and matching network

		<b>min.</b>	<b>typ.</b>	<b>max.</b>		
<b>Center frequency</b>	$f_C$	109,8	110,0	110,18	MHz	
<b>Minimum insertion attenuation</b>	$\alpha_{\min}$	—	6,8	10,0	dB	
<b>Pass bandwidth</b>	$\alpha_{\text{rel}} \leq 3,0 \text{ dB}$	$B_{3\text{dB}}$	3,75	4,0	—	MHz
	$\alpha_{\text{rel}} \leq 1,0 \text{ dB}$	$B_{1\text{dB}}$	—	3,1	—	MHz
<b>Amplitude ripple</b> (max peak to adjacent valley)	$\Delta\alpha$					
	$f_C \pm 1,6 \text{ MHz}$	—	0,5	—	dB	
<b>Group delay ripple</b>	$\Delta\tau$					
	$f_C \pm 1,6 \text{ MHz}$	—	45	80	ns	
<b>Relative attenuation</b> (relative to $\alpha_{\min}$ )	$\alpha_{\text{rel}}$					
	60,0 MHz ... 100,0 MHz	40	42	—	dB	
	100,0 MHz ... 105,5 MHz	36	41	—	dB	
	114,5 MHz ... 120,0 MHz	36	41	—	dB	
	120,0 MHz ... 160,0 MHz	38	43	—	dB	
<b>Temperature coefficient of frequency</b>	$TC_f$	—	-18	—	ppm/K	




Data Sheet

Normalized frequency response



Normalized frequency response (pass band)






Data Sheet

**Matching network** (element values may depend on pcb layout)

**50 Ω unbalanced:**




$$L_{s1} = 82 \text{ nH}$$

$$L_{p2} = 47 \text{ nH}$$

$$L_{p3} = 33 \text{ nH}$$

$$L_{s4} = 12 \text{ nH}$$

**50 Ω unbalanced :** (higher IL, but more attenuation in the upper stopband)



$$C_{p1} = 100 \text{ nF}$$

$$L_{s2} = 56 \text{ nH}$$

$$L_{s3} = 56 \text{ nH}$$

$$C_{p4} = 68 \text{ nF}$$



**SAW Components**

**B3802**

**Low-Loss Filter**

**110,0 MHz**

**Data Sheet**

**Published by EPCOS AG**

**Surface Acoustic Wave Components Division, SAW MC IS PD WL**

**P.O. Box 80 17 09, D-81617 München**

© EPCOS AG 2001. All Rights Reserved.

As far as patents or other rights of third parties are concerned, liability is only assumed for components per se, not for applications, processes and circuits implemented within components or assemblies.

The information describes the type of component and shall not be considered as assured characteristics.

Terms of delivery and rights to change design reserved.

For questions on technology, prices and delivery please contact the sales offices of EPCOS AG or the international representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our sales offices.