



Dual Digit LED Displays BD-A/C, BD-E/F Series

7-segment

Digit Size	Part No.		Chip		Absolute Maximum Ratings				Electro-optical Data (At 10mA)			Drawing No.
	Common Anode	Common Cathode	Material/Emitted Color	Peak Wave Length λ_p (nm)	$\Delta \lambda$ (nm)	Pd (mw)	If (mA)	Ifp (mA)	Vf (v)		Iv. Typ. Per.Seg. (mcd)	
									Typ.	Max.		
0.28" Dual-Digit	BD-E281RD	BD-F281RD	GaAsP/Red	655	40	80	40	200	1.7	2.0	0.5	DD-01
	BD-E285RD	BD-F285RD	GaP/ Bright Red	700	90	40	15	50	2.2	2.5	1.0	
	BD-E285RE	BD-F285RE										
	BD-E282RD	BD-F282RD	GaP/ Green	568	30	80	30	150	2.2	2.5	2.5	
	BD-E283RD	BD-F283RD	GaAsP/GaP/ Yellow	585	35	80	30	150	2.1	2.5	2.0	
	BD-E284RD	BD-F284RD	GaAsP/GaP/ Hi-Eff.Red	635	45	80	30	150	2.0	2.5	2.5	
			GaAsP/GaP/ Orange									
BD-E286RD	BD-F286RD	GaAlAs/ SH Super Red	660	20	80	30	150	1.7	2.5	5.0		
BD-E28DRD	BD-F28DRD	GaAlAs/ DH Super Red	660	20	80	30	150	1.7	2.5	6.0		
0.30" Dual-Digit	BD-A301ND	BD-C301ND	GaAsP/Red	655	40	80	40	200	1.7	2.0	0.6	DD-02
	BD-A305ND	BD-C305ND	GaP/ Bright Red	700	90	40	15	50	2.2	2.5	1.2	
	BD-A305NE	BD-C305NE										
	BD-A302ND	BD-C302ND	GaP/ Green	568	30	80	30	150	2.2	2.5	3.0	
	BD-A303ND	BD-C303ND	GaAsP/GaP/ Yellow	585	35	80	30	150	2.1	2.5	2.0	
	BD-A304ND	BD-C304ND	GaAsP/GaP/ Hi-Eff.Red	635	45	80	30	150	2.0	2.5	3.0	
			GaAsP/GaP/ Orange									
BD-A306ND	BD-C306ND	GaAlAs/ SH Super Red	660	20	80	30	150	1.7	2.5	6.0		
BD-A30DND	BD-C30DND	GaAlAs/ DH Super Red	660	20	80	30	150	1.7	2.5	7.0		
0.30" Dual-Digit	BD-A301ND-A	BD-C301ND-A	GaAsP/Red	655	40	80	40	200	1.7	2.0	0.6	DD-03
	BD-A305ND-A	BD-C305ND-A	GaP/ Bright Red	700	90	40	15	50	2.2	2.5	1.2	
	BD-A305NE-A	BD-C305NE-A										
	BD-A302ND-A	BD-C302ND-A	GaP/ Green	568	30	80	30	150	2.2	2.5	3.0	
	BD-A303ND-A	BD-C303ND-A	GaAsP/GaP/ Yellow	585	35	80	30	150	2.1	2.5	2.0	
	BD-A304ND-A	BD-C304ND-A	GaAsP/GaP/ Hi-Eff.Red	635	45	80	30	150	2.0	2.5	3.0	
			GaAsP/GaP/ Orange									
BD-A306ND-A	BD-C306ND-A	GaAlAs/ SH Super Red	660	20	80	30	150	1.7	2.5	6.0		
BD-A30DND-A	BD-C30DND-A	GaAlAs/ DH Super Red	660	20	80	30	150	1.7	2.5	7.0		
0.30" Dual-Digit	BD-E301RD	BD-F301RD	GaAsP/Red	655	40	80	40	200	1.7	2.0	0.6	DD-04
	BD-E305RD	BD-F305RD	GaP/ Bright Red	700	90	40	15	50	2.2	2.5	1.2	
	BD-E305RE	BD-F305RE										
	BD-E302RD	BD-F302RD	GaP/ Green	568	30	80	30	150	2.2	2.5	3.0	
	BD-E303RD	BD-F303RD	GaAsP/GaP/ Yellow	585	35	80	30	150	2.1	2.5	2.0	
	BD-E304RD	BD-F304RD	GaAsP/GaP/ Hi-Eff.Red	635	45	80	30	150	2.0	2.5	3.0	
			GaAsP/GaP/ Orange									
BD-E306RD	BD-F306RD	GaAlAs/ SH Super Red	660	20	80	30	150	1.7	2.5	6.0		
BD-E30DRD	BD-F30DRD	GaAlAs/ DH Super Red	660	20	80	30	150	1.7	2.5	7.0		
0.30" Dual-Digit	BD-E301RD-A	BD-F301RD-A	GaAsP/Red	655	40	80	40	200	1.7	2.0	0.6	DD-05
	BD-E305RD-A	BD-F305RD-A	GaP/ Bright Red	700	90	40	15	50	2.2	2.5	1.2	
	BD-E305RE-A	BD-F305RE-A										
	BD-E302RD-A	BD-F302RD-A	GaP/ Green	568	30	80	30	150	2.2	2.5	3.0	
	BD-E303RD-A	BD-F303RD-A	GaAsP/GaP/ Yellow	585	35	80	30	150	2.1	2.5	2.0	
	BD-E304RD-A	BD-F304RD-A	GaAsP/GaP/ Hi-Eff.Red	635	45	80	30	150	2.0	2.5	3.0	
			GaAsP/GaP/ Orange									
BD-E306RD-A	BD-F306RD-A	GaAlAs/ SH Super Red	660	20	80	30	150	1.7	2.5	6.0		
BD-E30DRD-A	BD-F30DRD-A	GaAlAs/ DH Super Red	660	20	80	30	150	1.7	2.5	7.0		
0.30" Dual-Digit	BD-E301RD-B	BD-F301RD-B	GaAsP/Red	655	40	80	40	200	1.7	2.0	0.6	DD-06
	BD-E305RD-B	BD-F305RD-B	GaP/ Bright Red	700	90	40	15	50	2.2	2.5	1.2	
	BD-E305RE-B	BD-F305RE-B										
	BD-E302RD-B	BD-F302RD-B	GaP/ Green	568	30	80	30	150	2.2	2.5	3.0	
	BD-E303RD-B	BD-F303RD-B	GaAsP/GaP/ Yellow	585	35	80	30	150	2.1	2.5	2.0	
	BD-E304RD-B	BD-F304RD-B	GaAsP/GaP/ Hi-Eff.Red	635	45	80	30	150	2.0	2.5	3.0	
			GaAsP/GaP/ Orange									
BD-E306RD-B	BD-F306RD-B	GaAlAs/ SH Super Red	660	20	80	30	150	1.7	2.5	6.0		
BD-E30DRD-B	BD-F30DRD-B	GaAlAs/ DH Super Red	660	20	80	30	150	1.7	2.5	7.0		



Dual Digit LED Displays BD-A/C, BD-E/F Series

7-segment

<p>DD-01 BD-^E/_F 28xRD</p> <p>Technical drawing of the BD-E28xRD dual digit LED display. It shows two views: a top view and a side view. The top view shows two 7-segment digits with a 10° angle between them. Dimensions include a total width of 15.00(591)mm, a height of 10.00(394)mm, and a segment height of 7.00(276)mm. Pin 1 is located at the bottom left. The side view shows a thickness of 7.62(30)mm and a mounting hole diameter of 10.16(400)mm. A detailed view of the LED segments shows a segment height of 6.1(240)mm and a segment width of 3.0(118)mm. The pin pitch is 2.54(10)mm. The pin configuration is shown as a 15-pin package with pins 1-15 and DP. The pin connections are: 15-A, 14-B, 13-C, 12-D, 11-E, 10-F, 9-G, 8-DP, 7-A, 6-B, 5-C, 4-D, 3-E, 2-F, 1-G.</p>	<p>DD-02 BD-^A/_C 30xND</p> <p>Technical drawing of the BD-A30xND dual digit LED display. It shows two views: a top view and a side view. The top view shows two 7-segment digits with a 10° angle between them. Dimensions include a total width of 15.50(610)mm, a height of 7.62(300)mm, and a segment height of 15.00(591)mm. Pin 1 is located at the bottom left. The side view shows a thickness of 10.16(400)mm and a mounting hole diameter of 10.16(400)mm. A detailed view of the LED segments shows a segment height of 7.20(283)mm and a segment width of 3.0(118)mm. The pin pitch is 1.7(07)x7=11.9(47)mm. The pin configuration is shown as a 15-pin package with pins 1-15. The pin connections are: 15-A, 14-B, 13-C, 12-D, 11-E, 10-F, 9-G, 8-DP, 7-A, 6-B, 5-C, 4-D, 3-E, 2-F, 1-G.</p>
<p>DD-03 BD-^A/_C 30xND-A</p> <p>Technical drawing of the BD-A30xND-A dual digit LED display. It shows two views: a top view and a side view. The top view shows two 7-segment digits with a 10° angle between them. Dimensions include a total width of 15.50(610)mm, a height of 7.62(300)mm, and a segment height of 15.00(591)mm. Pin 1 is located at the bottom left. The side view shows a thickness of 10.16(400)mm and a mounting hole diameter of 10.16(400)mm. A detailed view of the LED segments shows a segment height of 7.20(283)mm and a segment width of 3.0(118)mm. The pin pitch is 1.7(07)x7=11.9(47)mm. The pin configuration is shown as a 15-pin package with pins 1-15. The pin connections are: 15-A, 14-B, 13-C, 12-D, 11-E, 10-F, 9-G, 8-DP, 7-A, 6-B, 5-C, 4-D, 3-E, 2-F, 1-G.</p>	<p>DD-04 BD-^E/_F 30xRD</p> <p>Technical drawing of the BD-E30xRD dual digit LED display. It shows two views: a top view and a side view. The top view shows two 7-segment digits with a 10° angle between them. Dimensions include a total width of 15.50(610)mm, a height of 7.62(300)mm, and a segment height of 15.00(591)mm. Pin 1 is located at the bottom left. The side view shows a thickness of 10.16(400)mm and a mounting hole diameter of 10.16(400)mm. A detailed view of the LED segments shows a segment height of 7.20(283)mm and a segment width of 3.0(118)mm. The pin pitch is 2.54(100)mm. The pin configuration is shown as a 15-pin package with pins 1-15. The pin connections are: 15-A, 14-B, 13-C, 12-D, 11-E, 10-F, 9-G, 8-DP, 7-A, 6-B, 5-C, 4-D, 3-E, 2-F, 1-G.</p>
<p>DD-05 BD-^E/_F 30xRD-A</p> <p>Technical drawing of the BD-E30xRD-A dual digit LED display. It shows two views: a top view and a side view. The top view shows two 7-segment digits with a 10° angle between them. Dimensions include a total width of 15.50(610)mm, a height of 7.62(300)mm, and a segment height of 15.00(591)mm. Pin 1 is located at the bottom left. The side view shows a thickness of 10.16(400)mm and a mounting hole diameter of 10.16(400)mm. A detailed view of the LED segments shows a segment height of 7.20(283)mm and a segment width of 3.0(118)mm. The pin pitch is 2.54(100)mm. The pin configuration is shown as a 15-pin package with pins 1-15. The pin connections are: 15-A, 14-B, 13-C, 12-D, 11-E, 10-F, 9-G, 8-DP, 7-A, 6-B, 5-C, 4-D, 3-E, 2-F, 1-G.</p>	<p>DD-06 BD-^E/_F 30xRD-B</p> <p>Technical drawing of the BD-E30xRD-B dual digit LED display. It shows two views: a top view and a side view. The top view shows two 7-segment digits with a 10° angle between them. Dimensions include a total width of 15.50(610)mm, a height of 7.62(300)mm, and a segment height of 15.00(591)mm. Pin 1 is located at the bottom left. The side view shows a thickness of 10.16(400)mm and a mounting hole diameter of 10.16(400)mm. A detailed view of the LED segments shows a segment height of 7.20(283)mm and a segment width of 4.0±0.5(1574.0±.02)mm. The pin pitch is 2.54(100)mm. The pin configuration is shown as a 15-pin package with pins 1-15. The pin connections are: 15-A, 14-B, 13-C, 12-DP, 11-A, 10-D, 9-E, 8-F, 7-G, 6-DP, 5-A, 4-B, 3-C, 2-D, 1-G.</p>

NOTES: 1.All Dimensions are in millimeters(inches).
 3.Specifications are subject to change without notice.

2.Tolerance is ± 0.25mm(.010").
 4.NP:No Pin. 5.NC:No Connect.

AMERICAN BRIGHT