ADSL LINE TRANSFORMERS





- For use with Analog Devices AD20msp930 ADSL Chipset (Central Office)
- Excellent THD performance in a small footprint
- Designed to meet UL1950 and EN60950 supplementary insulation requirements for working voltages up to 250 Vrms

Electrical Specifications @ 25°C — Operating Temperature -40°C to 85°C												
Part Number	Mounting	Application	Turns Ratio (10-7):(1-4)		KHz, 0.1 V MIN)	Leakage Inductance @ 100 KHz, 0.1 V (MAX)	Longitudinal Balance					
			(± 2%)	(1-4) with 2-3 shorted	(10-7) with 8-9 shorted	(10-7) with 2-3, 1-4, 8-9 shorted	(10 KHz - 1.1 MHz)					
B2162	SMT	CO	1:1.1	2.03	1.75	7.5 µH	50 dB MIN					


Additional Specifications											
Part	THD Typical	Load Resistance	DC Resistar	nce (Ω - MAX)	Isolation Voltage	Insertion Loss 1					
Number	(Linearity)	(Ω)	(1-4) with 2-3 shorted	(10-7) with 8-9 shorted	(Vrms)	(dB @ 300 KHz)					
B2162	-80 dB @ 30 KHz	100	1.30	1.50	1500	<0.5					


¹ FrequencyResponse: ± 1.0 dB MAX, from 30 KHz to 1.1 MHz.

Mechanical

Schematic

B2162





Weight 6.2 grams Tape & Reel150/reel Tray60/tray

Dimensions: Inches

Unless otherwise specified, all tolerances are $\pm \frac{.010}{0.25}$

For More Information:

UNITED KINGDOM UNITED STATES FRANCE SINGAPORE TAIWAN, R.O.C. **HONG KONG DISTRIBUTOR** (Worldwide) (Northern Europe) (Southern Europe) (Southern Asia) (Northern Asia) (China/Hong Kong) 12220 World Trade Drive 1 & 2 Huxley Road 3F-4, No. 81, Sec. 1 9/F, Phase 2, Tai Sang Zone Industrielle 150 Kampong Ampat San Diego, CA 92128 The Surrey Research Park HsinTai Wu Road F-39270 #07-01/02 Shatin Warehouse Centre Guildford, Surrey GU2 5RE KA Centre U.S.A. Orgelet Hsi-Chih. Taipei Hsien 6 Wong Chuk Yeung Street http://www.pulseeng.com United Kingdom Singapore 368324 Taiwan, R.O.C. Fotan, Shatin, Hong Kong TEL: 44 1483 401700 TEL: 858 674 8100 TEL: 33 3 84 35 04 04 TEL: 65 6287 8998 Tel: 886 2 2698 0228 TEL: 852 2788 6588 FAX: 44 1483 401701 FAX: 858 674 8262 FAX: 33 3 84 25 46 41 FAX: 65 6280 0080 FAX: 886 2 2698 0948 FAX: 852 2776 1055

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.

² Transformers are shipped in trays, unless Tape & Reel packaging is specified by adding the suffix "T" to this part number (B2162T)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pulse:

B2162T B2162 B2162NL B2162NLT