


A range of diecast boxes in various sizes, manufactured in a robust aluminium alloy. These lightweight enclosures provide excellent screening against EMI/RFI and are therefore ideal housing for electronic components and circuits.
The close fitting lid is secured using countersunk screws.


Material
Box & Lid :Aluminium Alloy LM24
Screws :Mild Steel Zinc Plated M3.5x9
Finish :60-80 microns Powder coating

Admiralty Grey
BS4800 REF18B25


Black RAL 9005




SIZE - A,B,C,D




SIZE - J,K,L,M



SIZE - E,F,G,H



SIZE - N



SIZE - P, Q

Add letter after order code for colour required.
Black - E

TAPER 1.5° PER SIDE

Part No	Size	L	W	H	C1	C2	S1	S2	Wall Thickness	Taper
461-0010	A	88.9	34.9	29.5	79.4	25.4			1.5mm	Base to Lid
461-0020	B	114.5	64	29.5	104.6	54.1			1.5mm	Lid to Base
461-0030	C	115.7	90.5	54.9	104.6	79.4			1.5mm	Lid to Base
461-0040	D	115.3	64.5	54.9	103.4	52.5			2.0mm	Lid to Base
461-0050	E	171.5	120.6	54.9	160.5	109.6			2.0mm	Base to Lid
461-0060	F	171.5	120.6	105.7	160.5	109.6			2.0mm	Base to Lid
461-0070	G	222.3	146	55	211.5	135.3			2.0mm	Base to Lid
461-0080	H	222.3	146	105.7	211.5	135.3			2.0mm	Base to Lid
461-0090	J	275	175	65	264	164	132		2.0mm	Base to Lid
461-0100	K	139.7	101.6	76	128.7	90.6	64.4		2.0mm	Base to Lid
461-0110	L	165	127	76	154.1	116	77		2.0mm	Base to Lid
461-0120	M	120	100	35	108.3	88.2	50		2.0mm	Base to Lid
461-0130	N	250	250	100	238	238	80	160	2.5mm	Base to Lid
461-0140	P	80	55	25	70.5	45.5	40		1.5mm	Base to Lid
461-0150	Q	60	55	30	50.5	45.5	30		1.5mm	Base to Lid