

■ FEATURES

- High reliability
- Small size with high dielectric constant
- Low inductance
- Popular temperature coefficients available
- Wide operating temperature range
- High insulation resistance
- Case sizes: 0402, 0603, 0805, 1206, 1210



■ CHARACTERISTICS

Item	Characteristics		
	NPO / COG	X7R	Z5U
Operating Temperature Range	-55°C ~ +125°C	-55°C ~ +125°C	-25°C ~ +85°C
Temperature Coefficient	±30ppm/°C for C>20pF +120ppm, -40ppm/°C for C≤20pF	ΔC ±15% maximum over -55°C +125°C	ΔC ±56%-22% maximum over +10°C +85°C
Measuring Conditions for Capacitance and D.F.	1MHz, 1Vrms for C≤1,000pF 1KHz, 1Vrms for C>1,000pF	1KHz, 1Vrms	1KHz, 0.3Vrms
Dissipation Factor and Tangent of Loss Angle (Tan δ)	≥0.001 for C≥50pF ≤1.5(150/C + 7) × 10 ⁻² for C<50pF	≤0.025	≤0.030
Insulation Resis. After 60 sec. Charging at Rated Voltage 25°C	≥100GΩ or ≥1,000MΩ(C) whichever is less	≥100GΩ or ≥1,000MΩ(C) whichever is less	≥10GΩ or ≥1,000MΩ(C) whichever is less
Voltage Test 25°C	2.5 x rated voltage	2.5 x rated voltage	2.5 x rated voltage
Capacitance Aging	0	=1.5% per decade hour	=5% per decade hour

■ PART NUMBERING SYSTEM

C	C	5	0	2	N	1	0	1	J	/	R	E	E	L
Series		Voltage		Case Size	Temperature Coefficient	Value			Tolerance	Suffix				

■ CODES FOR CASE SIZE, TEMPERATURE COEFFICIENT, AND TOLERANCE

Case Size	Code
0805	1
1206	2
1210	3
0603	4
0402	5

Temperature Coefficient	Code
NPO / COG	N
X7R	B
Z5U	Z
Y5V	V

Tolerance	Code	Tolerance	Code
±0.25pF	C	±20%	M
±0.5pF	D	+80% -20%	Z
±5%	J	+100% -0%	P
±10%	K	GMV	V

Suffix	Code
Tape and Reel	/REEL
Bulk	-BK

For capacitance values below 10pF, use C or D.
GMV = Guaranteed Minimum Value


■ CAPACITANCE RANGES

Case Size	NPO / COG		X7R		Z5U (0805, 1206, 1210) / Y5V (0603)	
	50V	100V	50V	100V	50V	100V
0402	1.0pF~220pF		220pF~1000pF			---
0603	1.0pF~470pF		100pF~0.01 μ F		0.01 μ F~0.1 μ F	---
0805	1.0pF~1500pF	1.0pF~1000pF	100pF~0.1 μ F	100pF~.022 μ F	2700pF~0.15 μ F	---
1206	1.0pF~3900pF	1.0pF~2700pF	100pF~0.1 μ F	100pF~.047 μ F	8200pF~0.47 μ F	---
1210	4700pF~8200pF	3300pF~5600pF	0.12 μ F~0.22 μ F	.047 μ F~0.1 μ F	0.22 μ F~0.68 μ F	---


■ TOLERANCE AVAILABLE

Availability	NPO / COG				X7R			Z5U		
	± 0.25 pF	± 0.5 pF	$\pm 2\%$	$\pm 5\%$	$\pm 5\%$	$\pm 10\%$	$\pm 20\%$	$\pm 20\%$	+80% -20%	+100% -0%
Capacitance	<5pF	≤ 10 pF	>13pF	≥ 10 pF	All Values	All Values	All Values	All Values	All Values	All Values


■ DIMENSIONS



Configuration:



Reel Dimensions (mm):



Case Size	Dimensions (mm)			
	L (length)	W (width)	T (thickness) max.	E (termination)
0402	1.0 ± 0.2	0.5 ± 0.2	.35	0.5 ± 0.2
0603	1.52 ± 0.2	0.8 ± 0.2	.65	0.5 ± 0.2
0805	2.0 ± 0.2	1.2 ± 0.2	1.0	0.5 ± 0.2
1206	3.2 ± 0.2	1.6 ± 0.2	1.25	0.5 ± 0.2
1210	3.2 ± 0.2	2.5 ± 0.2	1.3	0.5 ± 0.2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Xicon:

[140-CC504N2.2C](#) [140-CC501N101J](#) [140-CC504N120J](#) [140-CC501Z473M](#) [140-CC504B472K](#) [140-CC505N4.0C](#)
[140-CC501N331J](#) [140-CC501N330J](#) [140-CC504B102K](#) [140-CC501N221J](#) [140-CC501N7.0D](#) [140-CC502B122K](#)
[140-CC501N4.0C](#) [140-CC501N4.7C](#) [140-CC501N2.2C](#) [140-CC501Z393M](#) [140-CC504N6.8D](#) [140-CC504N6.0D](#) [140-CC505N100D](#) [140-CC501N270J](#) [140-CC504B561K](#) [140-CC504N151J](#) [140-CC505N1.0C](#) [140-CC502B102K](#) [140-CC504N3.9C](#) [140-CC501N121J](#) [140-CC501N120J](#) [140-CC505B471K](#) [140-CC504N221J](#) [140-CC501N181J](#) [140-CC504N220J](#) [140-CC501N180J](#) [140-CC501N0.5C](#) [140-CC501N0.5C-RC](#) [140-CC501N1.0C-RC](#) [140-CC501N1.5C-RC](#) [140-CC501N100D-RC](#) [140-CC501N101J-RC](#) [140-CC501N150J-RC](#) [140-CC501N180J-RC](#) [140-CC501N2.0C-RC](#)
[140-CC501N2.2C-RC](#) [140-CC501N220J-RC](#) [140-CC501N270J-RC](#) [140-CC501N3.0C-RC](#) [140-CC501N3.3C-RC](#)
[140-CC501N3.9C-RC](#) [140-CC501N330J-RC](#) [140-CC501N390J-RC](#) [140-CC501N4.0C-RC](#) [140-CC501N4.7C-RC](#)
[140-CC501N470J-RC](#) [140-CC501N5.0D-RC](#) [140-CC501N560J-RC](#) [140-CC501N6.0D-RC](#) [140-CC501N6.8D-RC](#)
[140-CC501N680J-RC](#) [140-CC501N7.0D-RC](#) [140-CC501N8.0D-RC](#) [140-CC501N820J-RC](#) [140-CC501N9.0D-RC](#)
[140-CC504B102K-RC](#) [140-CC504B103K-RC](#) [140-CC504B122K-RC](#) [140-CC504B152K-RC](#) [140-CC504B182K-RC](#)
[140-CC504B221K-RC](#) [140-CC504B222K-RC](#) [140-CC504B271K-RC](#) [140-CC504B272K-RC](#) [140-CC504B331K-RC](#)
[140-CC504B332K-RC](#) [140-CC504B391K-RC](#) [140-CC504B392K-RC](#) [140-CC504B471K-RC](#) [140-CC504B472K-RC](#)
[140-CC504B561K-RC](#) [140-CC504B562K-RC](#) [140-CC504B681K-RC](#) [140-CC504B682K-RC](#) [140-CC504B821K-RC](#)
[140-CC504B822K-RC](#) [140-CC504N1.0C-RC](#) [140-CC504N1.5C-RC](#) [140-CC504N100D-RC](#) [140-CC504N101J-RC](#)
[140-CC504N120J-RC](#) [140-CC504N121J-RC](#) [140-CC504N150J-RC](#) [140-CC504N151J-RC](#) [140-CC504N180J-RC](#)
[140-CC504N181J-RC](#) [140-CC504N2.0C-RC](#) [140-CC504N2.2C-RC](#) [140-CC504N220J-RC](#) [140-CC504N270J-RC](#)
[140-CC504N3.0C-RC](#) [140-CC504N3.3C-RC](#) [140-CC504N3.9C-RC](#) [140-CC504N330J-RC](#)