

TOSHIBA

MICROWAVE SEMICONDUCTOR

TECHNICAL DATA

MICROWAVE POWER GaAs FET

JS8894-AS

FEATURES:

- HIGH POWER
P_{1dB} = 27.0 dBm at f = 23 GHz
- HIGH GAIN
G_{1dB} = 6.0 dB at f = 23 GHz
- SUITABLE FOR K-BAND AMPLIFIER
- ION IMPLANTATION
- CHIP FORM

RF PERFORMANCE SPECIFICATIONS (T_a = 25° C)

TYPE NUMBER				JS8894-AS (CHIP)		
CHARACTERISTIC	SYMBOL	CONDITION	UNIT	MIN.	TYP.	MAX.
Output Power at 1dB Com- pression Point	P _{1dB}	V _{DS} =7V f = 23GHz	dBm	26.0	27.0	-
Power Gain at 1dB Com- pression Point	G _{1dB}		dB	5.0	6.0	-
Drain Current	I _{DS}		A	-	0.36	0.52
Power Added Efficiency	η _{add}		%	-	15	-

ELECTRICAL CHARACTERISTICS (T_a = 25° C)

TYPE NUMBER				JS8894-AS (CHIP)		
CHARACTERISTIC	SYMBOL	CONDITION	UNIT	MIN.	TYP.	MAX.
Trans- Conductance	g _m	V _{DS} =3V I _{DS} =0.4A	mS	-	280	-
Pinch-off Voltage	V _{GSoff}	V _{DS} =3V I _{DS} =6mA	V	-2	-3.5	-5
Saturated Drain Current	I _{DSS}	V _{DS} =3V V _{GS} =0V	A	-	0.8	1.1
Gate to Source Breakdown Voltage	V _{GSO}	I _{GS} =-20μA	V	-5	-	-
Thermal Resistance	R _{th(c-c)}	Channel to case	°C/W	-	16	30

- ★ The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of TOSHIBA or others.
- ★ The information contained herein may be changed without prior notice. It is therefore advisable to contact TOSHIBA before proceeding with the design of equipment incorporating this product.




JS8894-AS

ABSOLUTE MAXIMUM RATINGS ($T_a = 25^\circ\text{C}$)


TYPE NUMBER			JS8894-AS (CHIP)
CHARACTERISTIC	SYMBOL	UNIT	RATING
Drain-Source Voltage	V_{DS}	V	12
Gate-Source Voltage	V_{GS}	V	-5
Drain Current	I_D	A	1.1
Total Power Dissipation ($T_c=25^\circ\text{C}$)	P_T	W	5.0
Channel Temperature	T_{ch}	$^\circ\text{C}$	175
Storage Temperature	T_{stg}	$^\circ\text{C}$	-65~175

POWER DISSIPATION VS. CASE TEMPERATURE



JS8894-AS

CHIP OUTLINE



ASSEMBLY PRECAUTIONS FOR CHIP

The operations must be performed in a clean and dry environment. The chips must be kept in the same environment when they are not used. All test instruments, assembly machines, benches, tweezers and operators should be grounded to avoid damage due to electrostatic discharge. Careful attention must be paid in handling chips with tweezers because GaAs is more brittle than Si.

DIE ATTACHMENT


Die attachment can be accomplished with Au-Sn preform in nitrogen atmosphere. The operating temperature must be $290 \pm 10^\circ\text{C}$ for the preform to be well melted. The operating time should be kept within one minute.

WIRE BONDING

Bonding should be performed with thermal compression wedge bonder in nitrogen atmosphere. The recommended conditions of wire bonding are as follows:

- (1) Operating temperature $200 \pm 10^\circ\text{C}$
- (2) Operating time 5 minutes max.
- (3) Bonding wire 25 μm diameter pure Au


OUTPUT POWER CHARACTERISTIC



JS8894-AS


JS8894-AS S-PARAMETERS (MAGN. and ANGLES)

$V_{DS} = 7 \text{ V}$, $I_{DS} = 0.4 \text{ A}$



JS8894-AS

JS8894-AS EQUIVALENT CIRCUIT (Includes normal bonding wires)



g_m	260	mS
τ	3.967	ps
R_g	0.209	Ω
R_s	0.159	Ω
R_d	0.359	Ω
R_{gs}	0.179	Ω
R_{gd}	0.001	Ω
R_{ds}	40.2	Ω
C_{gs}	2.6	pF
C_{gd}	0.164	pF
C_{ds}	0.992	pF
L_g	0.037	nH
L_s	0.002	nH
L_d	0.029	nH