

I. AAD130SD Configured For Single Output

Standard Models

AAD130SD-VW-YYYY

Tailored Models

AAD130SD- 60ZZZ

Custom Models

AAD130SD-61ZZZ

Voltage and Current Ratings		Standard Options
V W Codes	Volts Amps	Y Code Description
10	Not Available Not Available	A Current Sharing B PF Invert C Through Hole Mounting* G = Input and Option Connectors with Gold Pins J = Molex Output Connector with Gold Pins** K = Molex Output Connector with Standard Pins** M = Metric Mounting* O = PF Open Collector *Pemnut chassis mounting is standard **14A MAX current
20	3.3 32.0	
30	5.0 26.0	
40	12.0 12.0	
50	15.0 9.5	
60	24.0 6.0	
70	28.0 5.0	
80	36.0 4.0	
90	48.0 3.0	
		Tailored Units (no safety changes) ----- 60ZZZ, where ZZZ = Factory Assigned Number. Harnesses Added, Special test data, Etc
		Custom Units (safety critical changes) ----- 61ZZZ, where ZZZ = Factory Assigned Number

II. AAD130SD Configured For Dual Output

Standard Models

AAD130SD-V W-YYYY

Tailored Models

AAD130SD-60ZZZ

Custom Models

AAD130SD-61ZZZ

	Voltage and Current Ratings				Standard Options
V and W Codes	V Channel		W Channel		Y Code Description
	Volts	(V1) Amps	Volts	(V2) Amps	
1	Not Available		Not Available		A Current Sharing B PF Invert C Through Hole Mounting* G = Input and Option Connectors with Gold Pins J = Molex Output Connector with Gold Pins** K = Molex Output Connector with Standard Pins** M = Metric Mounting* O = PF Open Collector *Pemnut chassis mounting is standard **7A MAX current for V1, V2 outputs
2	3.3	16	3.3	16	
3	5.0	14	5.0	14	
4	12.0	6	12.0	6	
5	15.0	5	15.0	5	
6	24.0	3	24.0	3	
7	28.0	2.5	28.0	2.5	
8	36.0	2	36.0	2	
9	48.0	1.5	48.0	1.5	
					Tailored Units (no safety changes) ----- 60ZZZ, where ZZZ = Factory Assigned Number. Harnesses Added, Special test data, Etc.
					Custom Units (safety critical changes) ----- 61ZZZ, where ZZZ = Factory Assigned Number