SuperServer 6027TR-DTRF

Integrated Board

Super X9DRT-HF

Available Colors: Black

▸ Drivers & Utilities ▸ BIOS ▸ IPMI ▸ Tested Memory ▸ Tested HDD
▸ Manuals ▸ OS Certification Matrix ▸ GPU Kit Installation Guide

Key Features

Two hot-pluggable systems (nodes) in a 2U form factor. Each node supports the following:

1. Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and **E5-2600 v2** family†
2. Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
3. 3x PCI-E 3.0 (x8) slots (1x low-profile and 2x full-height full-length)
4. Intel® i350 Dual port Gigabit Ethernet
5. 6x 3.5" Hot-swap SATA3/SATA2 HDD Bays
6. 1280W Redundant Digital PS **Platinum Level (95%)**
7. Support 1 Full-height Full-length PCI-E x16 GPU card per node w/ GPU Kit

Note: Image above may show a varied configuration or optional parts, Please refer to parts list for standard parts included.

Specifications

Product SKUs	
SYS-6027TR-DTRF	▪ SuperServer 6027TR-DTRF (**Black**)

Motherboard	
Super X9DRT-HF	

Processor/Cache	
CPU	▪ Dual Socket R (LGA 2011) ▪ Intel® Xeon® processor E5-2600 and **E5-2600 v2** family† (up to 135W TDP *) * Please contact your Supermicro sales representative for additional details
Note	† BIOS version 3.0 or above is required
Cache	▪ Up to 30MB
System Bus	▪ QPI up to 8 GT/s

System Memory	
Memory Capacity	▪ 8x 240-pin DDR3 DIMM sockets ▪ Up to 512GB DDR3 ECC LRDIMM ▪ Up to 256GB DDR3 ECC Registered memory (RDIMM)
Memory Type	▪ 1866/1600/1333/1066/800MHz ECC DDR3 SDRAM 72-bit, 240-pin gold-plated DIMMs
DIMM Sizes	▪ 32GB, 16GB, 8GB, 4GB, 2GB, 1GB
Memory Voltage	▪ 1.5 V, 1.35 V
Error Detection	▪ Corrects single-bit errors ▪ Detects double-bit errors (using ECC memory)

On-Board Devices	
Chipset	▪ Intel® C602 Chipset
SATA	▪ SATA 2.0 & 3.0 with RAID 0, 1, 5, 10
IPMI	▪ Support for Intelligent Platform Management Interface v.2.0 ▪ IPMI 2.0 with virtual media over LAN and KVM-over-LAN support ▪ Nuvoton WPCM450 BMC
Network Controllers	▪ Intel® i350 Dual Port Gigabit Ethernet ▪ Virtual Machine Device Queues reduce I/O overhead ▪ Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output ▪ 1x Realtek RTL8201N PHY (dedicated IPMI)
Graphics	▪ Matrox G200eW

Input / Output (per Node)	
Serial ATA	▪ 2x SATA 3.0 ports (6Gbps) ▪ 4x SATA 2.0 ports (3Gbps)
LAN	▪ 2x RJ45 Gigabit Ethernet LAN ports ▪ 1x RJ45 Dedicated IPMI LAN port
USB	▪ 3x USB 2.0 ports total (2x rear + 1x Type A)
VGA	▪ 1x VGA port
Serial Port / Header	▪ 1x Fast UART 16550 port / 1 Header

Chassis	
Form Factor	▪ 2U Rackmount
Model	▪ **CSE-827HD-R1K28B**

Dimensions	
Width	▪ 17.25" (438mm)
Height	▪ 3.47" (88mm)
Depth	▪ 28.5" (724mm)
Gross Weight	▪ 85 lbs (38.6kg)
Available Colors	▪ Black

Front Panel	
Buttons	▪ Power On/Off button ▪ System Reset button ▪ UID button
LEDs	▪ Power status LED ▪ HDD activity LED ▪ 2x Network activity LEDs ▪ Universal Information (UID) LED

Expansion Slots (per Node)	
PCI-Express	▪ 3x PCI-E 3.0 (x8) slots (1x Low-profile and 2x Full-height Full-length)

Drive Bays (per Node)	
Hot-swap	▪ 6x 3.5" Hot-swap SATA3/SATA2 HDD trays

System Cooling	
Fans	▪ 4x 8cm heavy duty PWM fans with optimal fan speed control

Power Supply	
1280W Redundant High-efficiency Digital Power Supplies w/ PMBus 1.2	
AC Input	▪ 1000W Output @ 100-140V, 8-12A, 50-60Hz ▪ 1280W Output @ 180-240V, 6-8A, 50-60Hz
DC Output	▪ 1000W: +12V/83A; +5Vsb/4A ▪ 1280W: +12V/106.7A, +5Vsb/4A
Certification	80 PLUS PLATINUM, 9 Digital! **Platinum Certified** [Test Report]

System BIOS	
BIOS Type	▪ 128Mb SPI Flash EEPROM with AMI BIOS
BIOS Features	▪ Plug and Play (PnP) ▪ APM 1.2 ▪ PCI 2.2 ▪ ACPI 1.0 / 2.0 ▪ USB Keyboard support ▪ SMBIOS 2.3 ▪ UEFI

Operating Environment / Compliance	
RoHS	▪ RoHS Compliant
Environmental Spec.	▪ Operating Temperature: 10°C to 35°C (50°F to 95°F) ▪ Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) ▪ Operating Relative Humidity: 8% to 90% (non-condensing) ▪ Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List

See Parts List

Copyright © 2015 Super Micro Computer, Inc.
Information in this document is subject to change without notice.
Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.