

DUAL ENTRY SOLENOID KEY OPERATED SAFETY INTERLOCK NOMENCLATURE

GK

BODY / INDICATOR		CONDUIT / SEAL		BASIC 		HEAD		KEY		TYPE / OVER-RIDE		SOLENOID VOLTAGE		MODIFICATION CODE 	
L	HEAD TO LEFT - WITH INDICATORS	A	1/2 NPT - VITON SEALS	2	2 SNAP ACTION DPDT	L	OPENING TO FRONT AND TOP	6	STRAIGHT	A	SOLENOID UNLOCK WITH SCREWDRIVER	1	12 VDC	F04	
R	HEAD TO RIGHT - WITH INDICATORS	B	PG 13.5 - VITON SEALS	3	2 SLOW ACTING SPDT BBM	M	OPENING TO RIGHT AND TOP	7	90 DEGREE		SLOT OVER-RIDE	2	24 VDC	F05	
F	HEAD TO LEFT - WITHOUT INDICATORS	C	20 MM - VITON SEALS	6	SLOW ACTING 2 NC	N	OPENING TO BACK AND TOP	8	UP - DOWN, SPRING LOADED	B	SOLENOID UNLOCK WITHOUT OVER-RIDE	3	48 VDC	FW	
G	HEAD TO RIGHT - WITHOUT INDICATORS	D	PF 1/2 - VITON SEALS	10	SLOW ACTING 4 NC	P	OPENING TO LEFT AND TOP	9	SIDE - SIDE, SPRING LOADED	S	SOLENOID LOCK WITH SCREWDRIVER	4	120 VAC		
		E	1/2 NPT - BUNA-N SEALS	12	SLOW ACTING 2 NC - 1 NO BBM			X	NO KEY	T	SLOT OVER-RIDE	6	240 VAC		
		F	PG 13.5 - BUNA-N SEALS	14	SLOW ACTING 2 NC - 2 NO BBM						SOLENOID LOCK WITHOUT OVER-RIDE				
		G	20 MM - BUNA-N SEALS	15	SLOW ACTING 2 NC - 2 NO BBM - GOLD										
		H	PF 1/2 - BUNA-N SEALS	16	SLOW ACTING 3 NC - 1 NO BBM										
				30	2 SLOW ACTING 4 NC - GOLD										
				32	2 SLOW ACTING 2 NC - 1 NO BBM - GOLD										
				34	2 SLOW ACTING 2 NC - 2 NO BBM - GOLD										
				36	2 SLOW ACTING 3 NC - 1 NO BBM - GOLD										
				40	2 SLOW ACTING 4 NC										
				42	2 SLOW ACTING 2 NC - 1 NO BBM										
				44	2 SLOW ACTING 2 NC - 2 NO BBM										
				46	2 SLOW ACTING 3 NC - 1 NO BBM										

NOTES

- 1 - ZINC DIECAST BODY AND HEAD WITH STEEL COVER. BODY, HEAD AND COVER FINISHED WITH EPOXY PAINT
- 2 - PROVIDED WITH PLASTIC SNAP FIT COVER TO PLUG UNUSED KEY ENTRY WINDOW
-  THE LEFT INDICATOR IS GREEN AND THE RIGHT INDICATOR IS RED. NOT PRESENT ON BODY/INDICATOR CODES F OR G
- 4 - MAXIMUM OPERATING FREQUENCY (Fmax) = 100 OPS/MIN
- 5 - INSERTION FORCE = 35 N
- EXTRACTION FORCE = 28 N
- 6 LB
- MAXIMUM SOLENOID LOCKING FORCE = 1000 N
- 224 LB
-  ROTATE 1/4 TURN CLOCKWISE TO UNLOCK DEVICES WITH HEAD TO LEFT, SOLENOID UNLOCK AND DEVICES WITH HEAD TO RIGHT, SOLENOID LOCK. ROTATE 1/4 TURN COUNTERCLOCKWISE TO UNLOCK DEVICES WITH HEAD TO LEFT, SOLENOID LOCK AND DEVICES WITH HEAD TO RIGHT, SOLENOID UNLOCK.
- NOT PRESENT ON TYPE/OVER-RIDE CODES B OR T
-  SWITCH MUST OPERATE BEFORE REACHING MINIMUM INSERTION DISTANCE
- 8 - T-15 TAMPERPROOF TORX DRIVER BIT PROVIDED
-  ELECTRICAL RATINGS ARE FOR BASIC SWITCHES
- 10 - MINIMUM SOLENOID VOLTAGE = 80% DC / 85% AC OF RATED VOLTAGE
- MAXIMUM SOLENOID VOLTAGE = 110% OF RATED VOLTAGE
- SOLENOID POWER = 12 WATTS NOMINAL
-  SEE PAGES 10, 11, 12 AND 13 FOR CIRCUIT DIAGRAMS
- 12 - NO CHANGES CAN BE MADE TO THIS DRAWING WITHOUT JOINT FREEPORT / NEWHOUSE APPROVAL
-  THE LEFT INDICATOR IS YELLOW AND THE RIGHT INDICATOR IS RED
-  10-PIN CONNECTOR, BRAD HARRISON PART NO.3R1006AZ1F010 OR EQUIVALENT
-  4-PIN CONNECTOR, WOODHEAD PART NO.80599-19 OR MOLEX PART NO.08631MZ1 OR EQUIVALENT
-  5-PIN CONNECTOR, BRAD HARRISON PART NO.41310 OR EQUIVALENT
-  CONNECTOR INSTALLED IN BOTTOM CONDUIT HOLE
-  CONNECTOR INSTALLED IN SIDE CONDUIT HOLE
-  FOR CONNECTOR AND CIRCUIT DETAILS OF MODIFICATION CODE, REFER PAGE 14 FOR CODE F05, PAGE 15 FOR CODE FW AND PAGE 16 FOR CODE F04

ELECTRICAL RATING 				ENVIRONMENTAL RATINGS		APPROVALS    IEC 947-5-1 EN60947-5-1
AC		DC		IP68 NEMA 1, 4, 6P, 12 & 13		
A300	AC 15	Q300	DC 13	TEMP RANGE -25°C TO 40°C		
Ue	Ie	Ue	Ie	-13°F TO 104°F		
(VOLTS)	(AMPS)	(VOLTS)	(AMPS)	STORAGE -40°C TO 120°C		
				-40°F TO 248°F		
120	6	24	2.9	SHOCK: 50G PER IEC 68-2-27		
240	3	125	.55	VIBRATION: 10G PER IEC 68-2-6		
		250	.27			
Ith = 10 A						

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

FED. MFG. CODE 91929

 **MICRO SWITCH**
a Honeywell Division

CATALOG LISTING

SWITCH - DOOR INTERLOCK

GK SERIES CHART 4

THIRD ANGLE PROJECTION

SCALE NTS




DO NOT SCALE PRINT

TOLERANCES
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE 1

NO PLACES	ONE PLACE	TWO PLACES	THREE PLACES	FOUR PLACES
±.0005	±.001	±.002	±.005	±.01
±.0005	±.001	±.002	±.005	±.01

DESIGN UNITS ☒ SI METRIC ☐ US CUSTOMARY

WEIGHT 1.5 kg / 3.3 LB






TOP KEY ENTRY

FRONT KEY ENTRY

BODY / INDICATOR CODES R OR G

[illegible]

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.			
FED. MFG. CODE 91929		CATALOG LISTING	
		SWITCH - DOOR INTERLOCK	
		GK SERIES CHART 4	
		NO PLACES 1.1 1/4 ONE PLACE 2.1 0.47-0.16 TWO PLACES 3.1 0.15-0.08 THREE PLACES ANGLES SI METRIC ☒ US CUSTOMARY ☐ DESIGN UNITS WEIGHT 1,5 kg / 3.3 LB	




TOP KEY ENTRY

FRONT KEY ENTRY


BODY / INDICATOR CODES L OR F

[illegible]

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.		<table><tr><td>DIM.</td><td>TOL.</td><td>DIM.</td><td>TOL.</td></tr><tr><td>mm / in</td><td>mm / in</td><td>mm / in</td><td>mm / in</td></tr><tr><td>NO PLACES</td><td>1 / 64</td><td>1.1</td><td>0.003</td></tr><tr><td>TWO PLACES</td><td>1 / 32</td><td>1.151</td><td>0.003</td></tr><tr><td>THREE PLACES</td><td>0.151 / .006</td><td>1.151</td><td>0.151 / .005</td></tr><tr><td>ANGLES</td><td></td><td></td><td></td></tr></table>		DIM.	TOL.	DIM.	TOL.	mm / in	mm / in	mm / in	mm / in	NO PLACES	1 / 64	1.1	0.003	TWO PLACES	1 / 32	1.151	0.003	THREE PLACES	0.151 / .006	1.151	0.151 / .005	ANGLES			
DIM.	TOL.	DIM.	TOL.																								
mm / in	mm / in	mm / in	mm / in																								
NO PLACES	1 / 64	1.1	0.003																								
TWO PLACES	1 / 32	1.151	0.003																								
THREE PLACES	0.151 / .006	1.151	0.151 / .005																								
ANGLES																											
FED. MFG. CODE 91929	CATALOG LISTING	<table><tr><td>SI METRIC</td><td>US CUSTOMARY</td></tr><tr><td>☒</td><td>☐</td></tr></table>		SI METRIC	US CUSTOMARY	☒	☐																				
SI METRIC	US CUSTOMARY																										
☒	☐																										
MICRO SWITCH a Honeywell Division	SWITCH - DOOR INTERLOCK	GK SERIES CHART 4																									
		DESIGN UNITS ☒ WEIGHT 1.5 kg / 3.3 lb																									





WITH KEY IN FRONT ENTRY POSITION




WITH KEY IN TOP ENTRY POSITION

HEAD CODE L




WITH KEY IN FRONT ENTRY POSITION



WITH KEY IN TOP ENTRY POSITION


HEAD CODE M




PTC/CAD 3D		DRAWING NUMBER		ISSUE 5254		MKG SERIES CHART 4	
DRAWN		PAGE 4 OF 16		RELEASE NO. PR-23758		REPLACES -	
REVISIONS							
N	0047583	SSK	04FEB09	P	0065737	PRS	31MAY10
R	0083578	MSR	10NOV11				
MAN	28SEP08	CHECK	CMH 12MAY09	CHECK	PRS 04FEB09	CHECK	CMH 10NOV11

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.															
FED. MFG. CODE 91929															
MICRO SWITCH a Honeywell Division															
CATALOG LISTING															
SWITCH - DOOR INTERLOCK															
GK SERIES CHART 4															
DESIGN UNITS ☒ SI METRIC ☐ US CUSTOMARY															
WEIGHT 1,5 kg / 3.3 LB															

THIRD ANGLE PROJECTION			
SCALE 2 : 1			
DO NOT SCALE PRINT			
TOLERANCES			
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE :			
NO PLACES	2	1/16	0.001
ONE PLACE	1/16	0.0156	0.0005
TWO PLACES	1/32	0.0078	0.00025
THREE PLACES	1/64	0.0039	0.0001
ANGLES	1/16	0.0078	0.0001
DESIGN UNITS ☒ SI METRIC ☐ US CUSTOMARY			
WEIGHT 1,5 kg / 3.3 LB			





WITH KEY IN FRONT ENTRY POSITION




WITH KEY IN TOP ENTRY POSITION


HEAD CODE N



WITH KEY IN FRONT ENTRY POSITION



WITH KEY IN TOP ENTRY POSITION



HEAD CODE P

[illegible]

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

FED. MFG. CODE 91929

MICRO SWITCH
a Honeywell Division

SWITCH - DOOR INTERLOCK

CATALOG LISTING

GK SERIES CHART 4

DIM.	TOL.	DIM.	TOL.
mm / in.		mm / in.	
NO PLACES	1	1/64	0.003
ONE PLACE	1.1	1/32	0.005
TWO PLACES	1.2	0.0010	0.0010
THREE PLACES	0.151/006	1.111	0.131/005
ANGLES			

SI METRIC








DESIGN UNITS ☒

US CUSTOMARY

☐

WEIGHT 1.5 KC / 2.2 LB

KEY CODE 6




FRONT KEY ENTRY

TOP KEY ENTRY



THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.			
FED. MFG. CODE 91929		CATALOG LISTING	
MICRO SWITCH a Honeywell Division		SWITCH - DOOR INTERLOCK	
DESIGN UNITS ☒ SI METRIC		US CUSTOMARY ☐	
WEIGHT 1.5 KG / 3.3 LB		GK SERIES CHART 4	

THIRD ANGLE PROJECTION			
SCALE 2 : 1			
DO NOT SCALE PRINT			
TOLERANCES APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE 1			
NO PLACES	1	1/16	1/16
ONE PLACE	1/16	1/16	1/16
TWO PLACES	1/32	1/32	1/32
THREE PLACES	1/64	1/64	1/64
ANGLES	1/16	1/16	1/16



KEY CODE 7



FRONT KEY ENTRY



TOP KEY ENTRY









THIRD ANGLE PROJECTION			
SCALE 2 : 1			
DO NOT SCALE PRINT			
TOLERANCES			
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE 1			
	MM	TOL	MM
NO PLACES		1/16	1/16
ONE PLACE	1/16	0.0156	0.0156
TWO PLACES	1/32	0.0078	0.0078
THREE PLACES	1/64	0.0039	0.0039
DESIGN UNITS	SI METRIC	US CUSTOMARY	
	☒	☐	
WEIGHT 1,5 KG / 3,3 LB			

PTC/CAD 3D	DATE	LOC 98	CHECK	CMH	12MAY98	CHECK	CMH	04FEB09	CHECK	CMH	10NOV11	RELEASE NO. PR-23758	PAGE 7 OF 16	ISSUE 5254	DRAWING NUMBER	REPLACES	-
PTC/CAD 3D	DATE	LOC 98	CHECK	CMH	12MAY98	CHECK	CMH	04FEB09	CHECK	CMH	10NOV11	RELEASE NO. PR-23758	PAGE 7 OF 16	ISSUE 5254	DRAWING NUMBER	REPLACES	-

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.		CATALOG LISTING	
FED. MFG. CODE 91929		SWITCH - DOOR INTERLOCK	
MICRO SWITCH a Honeywell Division		GK SERIES CHART 4	

ANSI Y14.5M-1982 APPLIES





KEY CODE 8



TOP KEY ENTRY


FRONT KEY ENTRY

KEY CODE 9





R150,00 MIN DOOR RADIUS

R250,00 MIN DOOR RADIUS




62,58 MIN INSERTION DISTANCE
2.464
58,68 MAX INSERTION DISTANCE
2.310




FRONT KEY ENTRY

TOP KEY ENTRY


THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.				CATALOG LISTING			
FED. MFG. CODE 91929		MICRO SWITCH a Honeywell Division		SWITCH - DOOR INTERLOCK		GK SERIES CHART 4	
NO PLACES		DESIGN UNITS		SI METRIC		US CUSTOMARY	
ONE PLACE		X		X			
TWO PLACES		X.X		X.X		X.X	
THREE PLACES		X.XX		X.XX		X.XX	
ANGLES							
WEIGHT		1,5 KG / 3,3 LB					




BODY / INDICATOR CODES - L OR R
TYPE / OVER-RIDE CODES - A OR B
DIAGRAMS SHOWN WITH KEY INSERTED AND LOCKED




SWITCH CODE - 2




SWITCH CODE - 3 OR 4




SWITCH CODE - 6




SWITCH CODE - 10




SWITCH CODE - 12




SWITCH CODE - 14




SWITCH CODE - 16




SWITCH CODE - 30 OR 40



SWITCH CODE - 32 or 42




SWITCH CODE - 34 or 44



SWITCH CODE - 36 or 46

BODY / INDICATOR CODES - F OR G
TYPE / OVER-RIDE CODES - A OR B
DIAGRAMS SHOWN WITH KEY INSERTED AND LOCKED



BODY / INDICATOR CODES - L OR R
TYPE / OVER-RIDE CODES - S OR T
DIAGRAMS SHOWN WITH KEY INSERTED AND LOCKED

PTC/CAD 3D
DRAWN
MAM
LOC 198
21 SEP 06
DVM
CHECK
PRG
0803578
31 MAY 10
0065737
04 FEB 09
SS
0047583
M
12 OF 16
PAGE
10 NOV 11
RELEASE NO. PR-23758
CMH
REPLACES

REVISIONS
M 0047583
SS
04 FEB 09
P 0065737
D 0065737
31 MAY 10
0803578

ISSUE
5254
MGM SERIES CHART 4

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.			
FED. MFG. CODE 91929		CATALOG LISTING	
MICRO SWITCH a Honeywell Division		SWITCH - DOOR INTERLOCK	
DESIGN UNITS		GK SERIES CHART 4	
SI METRIC		US CUSTOMARY	
WEIGHT 1.5 KG / 3.3 LB			


THIRD ANGLE PROJECTION			
SCALE NTS			
DO NOT SCALE PRINT			
TOLERANCES			
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE 1			
NO PLACES	2	1/4	2.2
ONE PLACE	1.2	0.015	0.38
TWO PLACES	1.22	0.015	0.38
THREE PLACES	1.222	0.015	0.38
ANGLES			





CATALOG LISTING
GK SERIES CHART 4
PAGE 14 OF 16
REPLACES -
CMH 10NOV11
CHECK 04FEB09
PRG 04FEB09
CHECK 9 DEC 99
JAF
CHECK 9 DEC 99
LJK
PTC/CAD 3D
DRAWN

REVISIONS
N 0047583
SSK 04FEB09
P 0065737
PRS 31MAY10
R 0083578
MBH 10NOV11


MODIFICATION CODE: F05




SWITCH DIAGRAM STATE
IS CLOSED AND LOCKED





300V 7A
BRAD-HARRISON PART NO. 3R1006A21F010
OR EQUIVALENT

THIRD ANGLE PROJECTION				
				
SCALE		NTS		
DO NOT SCALE PRINT				
TOLERANCES				
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE :				
	DIM.	TOL	DIM.	TOL
	mm	mm / in	in	mm / in
NO PLACES	X	1 / 0.04	X.X	0.01 / 0.03
ONE PLACE	X.X	0.1 / 0.016	X.XX	0.001 / 0.015
TWO PLACES	X.XX	0.01 / 0.0008	X.XXX	0.0001 / 0.0015
THREE PLACES				
ANGLES				
SI METRIC		US CUSTOMARY		
DESIGN UNITS		☒		
		☐		
WEIGHT 2,3 kg / 5 LB MAX				

MODIFICATION CODE: F04



SWITCH DIAGRAM STATE
IS CLOSED AND LOCKED



300V 7A
BRAD-HARRISON PART NO. 3R1006A21F010
OR EQUIVALENT

THIRD ANGLE PROJECTION																					
SCALE		NTS																			
DO NOT SCALE PRINT																					
TOLERANCES																					
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE :																					
<table><tr><th>DIM. mm</th><th>TOL mm / in</th></tr><tr><td>NO PLACES</td><td>X 1 / .04</td></tr><tr><td>ONE PLACE</td><td>X .X 0.1 / .016</td></tr><tr><td>TWO PLACES</td><td>X .XX 0.01 / .006</td></tr><tr><td>THREE PLACES</td><td></td></tr></table>		DIM. mm	TOL mm / in	NO PLACES	X 1 / .04	ONE PLACE	X .X 0.1 / .016	TWO PLACES	X .XX 0.01 / .006	THREE PLACES		<table><tr><th>DIM. in</th><th>TOL mm / in</th></tr><tr><td>X</td><td>0.8 / .03</td></tr><tr><td>X.X</td><td>0.38 / .015</td></tr><tr><td>X.XX</td><td>0.13 / .005</td></tr></table>		DIM. in	TOL mm / in	X	0.8 / .03	X.X	0.38 / .015	X.XX	0.13 / .005
DIM. mm	TOL mm / in																				
NO PLACES	X 1 / .04																				
ONE PLACE	X .X 0.1 / .016																				
TWO PLACES	X .XX 0.01 / .006																				
THREE PLACES																					
DIM. in	TOL mm / in																				
X	0.8 / .03																				
X.X	0.38 / .015																				
X.XX	0.13 / .005																				
SI METRIC DESIGN UNITS ☒		US CUSTOMARY ☐																			
WEIGHT 2,3 kg / 5 LB MAX																					