


# CCM04 MKII



The CCM04 without card guidance is used where space is at a premium and the card guidance can be built around the connector (rather than provided by the connector itself).

The CCM04 low profile without card guidance is dedicated to applications where the overall height of the connector is paramount. A range of low profile CCM04 connectors are available with 1.25 mm thick moldings.

The wide choice of contact configurations and molding heights suit a broad range of applications.

## Features

- Available in a variety of molding heights from 1.25 mm to 5 mm.
- The integrated card detection switch (optional) is sealed against dust and grit.
- By using an inlay finish in the contact area, the life of the precious metal is extended by more than 10 times that of standard gold plating.
- The height of the contact above the insulator is 0.75 mm, so allowing a wider tolerance for the card entry slot.
- The contact area is spooned to reduce the risk of accidental (or deliberate) damage, and to optimize the electrical connection with the card.
- The tip of the contact is protected by the molding so that it cannot catch on the card as the card is being inserted.
- The contact design ensures a consistent and reliable contact force over the life of the connector.
- Robustly formed printed circuit tails are well protected by the insulator body: a coplanarity of  $\pm 0.05$  mm is guaranteed.
- The moldings are made from high temperature thermoplastic suited for infrared and convection soldering processes.
- With tape and reel packaging as standard, the connectors are designed to be automatically picked & placed.

| Construction                          |                                                                                                                                  |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Contacts                              | Copper alloy                                                                                                                     |
| Plating                               | Contact area : Gold alloy inlay<br>Terminals : Tin lead (2μ min)                                                                 |
| Moldings                              | High temp. thermoplastic UL 94V-0 rated                                                                                          |
| Mechanical data                       |                                                                                                                                  |
| Number of Contacts                    | 6, 8 or 16                                                                                                                       |
| Mechanical life                       | 50,000 cycles min                                                                                                                |
| Durability of inlay                   | 5,000 cycles min (see note 1)                                                                                                    |
| Contact force                         | 0.25 N min / 0.5 N max                                                                                                           |
| Card detection switch actuation force | 0.8 N max for actuation (end travel switch actuates when card is 0.9 mm from card stop) 1.8 N max for complete depression        |
| Vibration 50m/s <sup>2</sup>          | Frequency 10 to 500 Hz. Acceleration<br>Duration 6 hours - amplitude 0.35 mm<br>Max electrical discontinuity 1μs                 |
| Shock                                 | Peak value 500 m/s <sup>2</sup> - Duration 11 ms<br>3 shocks in each direction of each axis<br>Max electrical discontinuity 1 μs |
| Electrical data                       |                                                                                                                                  |
| Insulation resistance                 | 1,000 MΩ min                                                                                                                     |
| Contact resistance max                | 100 mΩ max                                                                                                                       |
| Switching current                     | 10 μA min / 1 A max                                                                                                              |
| Dielectric strength                   | 750 Vrms min                                                                                                                     |
| Card detection switch                 | Normally open (closes on card insertion)                                                                                         |
| Switch contact resistance             | 100mΩ max                                                                                                                        |
| Dielectric switch contacts            | 250 Vrms min                                                                                                                     |
| Maximum switch power                  | 0.2 VA                                                                                                                           |
| Environmental data                    |                                                                                                                                  |
| Operating temperature                 | -40°C to +85°C                                                                                                                   |
| Soldering temperature                 | Temperature/time profile acc. to CECC00802 para. 6.1, Fig. 3 with peak temperature 250°C                                         |
| Damp heat                             | IEC 512 test number 11c (10 days)                                                                                                |
| Salt mist                             | IEC 512 test number 11f (96 hours)                                                                                               |
| Card detection switch                 | Sealed IP 54 For CCM04 1889 & 1905<br>Sealed against dust for other versions                                                     |

Note 1: Inlay (precious metal) rating is based on a very abrasive card being used and is intended to represent worst case.

# CCM04 MKII

| Ordering code  |           |                |                |                |                |
|----------------|-----------|----------------|----------------|----------------|----------------|
|                |           | Without Switch |                | With Switch    |                |
| Molding Height | SMT Tails | 2 x 3 contacts | 2 x 4 contacts | 2 x 4 contacts | 2 x 8 contacts |
| 1.25 mm        | Standard  | CCM04-1801     | CCM04-1814     | CCM04-1889     | CCM04-1905     |
| 1.25 mm        | Straight  | CCM04-1800*    | CCM04-1813*    | CCM04-1888*    |                |
| 2.00 mm        | Standard  | CCM04-5004**   | CCM04-1415*    |                |                |
| 2.75 mm        | Straight  | CCM04-1200     | CCM04-1217*    | CCM04-1316     | CCM04-1333*    |
| 2.75 mm        | Standard  | CCM04-1201     | CCM04-1218     | CCM04-1317     | CCM04-1334     |
| 3.50 mm        | Standard  | CCM04-1202     | CCM04-1219*    | CCM04-1318     |                |
| 4.25 mm        | Standard  | CCM04-1203*    | CCM04-1220     | CCM04-1319*    |                |
| 5.00 mm        | Standard  |                | CCM04-1221     | CCM04-1320     |                |

\*Note: On request

\*\*Note: Replaced by CCM04-5102 (see page 53)

## Packaging

Connectors without a switch are packaged in accordance with EIA 481-2 or IEC 286-3.



Connectors with a switch are packaged in accordance with EIA 481-3 or IEC 286-3

Standard packaging is in tape and reel. A modification code is added to the part number that indicates reel packaging and the number of components per reel (which varies according to the molding height).

Example: A CCM04 with 8 contacts plus switch and a molding height of 3.50 mm has a part number CCM04-1318-R751.

| Molding Height | SMT Tails | Without Switch |                | With Switch    |                | N° reels per box |
|----------------|-----------|----------------|----------------|----------------|----------------|------------------|
|                |           | 2 x 3 contacts | 2 x 4 contacts | 2 x 4 contacts | 2 x 8 contacts |                  |
| 1.25 mm        | Standard  | R182 (1800pcs) | R132 (1300pcs) | R102 (1000pcs) | R651 (650pcs)  | 5                |
| 1.25 mm        | Straight  | R182 (1800pcs) | R132 (1300pcs) | R102 (1000pcs) |                | 5                |
| 2.00 mm        | Standard  | R122 (1200pcs) | R901 (900pcs)  |                |                | 5                |
| 2.75 mm        | Straight  | R122 (1200pcs) | R901 (900pcs)  | R801 (800pcs)  | R451 (450pcs)  | 5                |
| 2.75 mm        | Standard  | R122 (1200pcs) | R901 (900pcs)  | R801 (800pcs)  | R451 (450pcs)  | 5                |
| 3.50 mm        | Standard  | R112 (1100pcs) | R801 (800pcs)  | R751 (750pcs)  |                | 5                |
| 4.25 mm        | Standard  | R951 (950pcs)  | R701 (700pcs)  | R651 (650pcs)  |                | 5                |
| 5.00 mm        | Standard  |                | R651 (650pcs)  | R601 (600pcs)  |                | 5                |

R = Reel



| Reel Diameter | Reel Width | X      | Y      | Z   |
|---------------|------------|--------|--------|-----|
| 360 mm        | 24.4 mm    | 344 mm | 350 mm | 152 |

## Dimensional Drawings

RECOMMENDED PCB LAYOUT  
(Component side)

Plastic outline  
Contact foot area  
0.8 x 1  
Pad

23.2  
5.5 2.5 5.5  
8.0

C5 C6 C7 C1 C2 C3

02 03 04

Prohibited area

Contact location according to  
ISO 7866-2 & ENV 1375-1 & GSM-II

3.81 3.81 7.79  
25.5

**CCM04-1814 2 x 4 contacts**

The drawing includes three main views:

- Top View:** Shows the overall dimensions of the connector. The total width is 23.6. The central area is labeled "Date Code area" and contains the code "XXXXXX". The bottom edge features a "Pick and place area" with a diameter of  $\varnothing 3.5$ . Dimensions for the contact rows are given as 2.54, 2.54, 2.54, and 2.54.
- Side View:** Shows the profile of the connector. The total height is 17.8. The mounting tab has a width of 0.8 and a thickness of 0.25. The mating condition shows two contact points with a distance of 3.81 between them and a 30° angle. The overall length is 25.5 ± 0.2.
- DETAIL A:** A magnified view of the contact tip at Scale 10. It shows a width of 0.8 and a thickness of 0.25.

**CCM04-1814 PCB layout**

RECOMMENDED PC BOARD LAYOUT  
(Component side)

Plastic outline  
Contact foot area  
0.8 x 1  
Pad

23.2  
15  
15  
5.5  
2.5  
5.5  
1.8  
13  
1.3  
0.2  
2.54  
2.54  
2.54  
2.54  
C8  
C7  
C6  
C5  
C4  
C3  
C2  
C1  
Prohibited area  
Contact location according to  
ISO 7815-2 & ENV 1375-1 & G5MMH-1  
3.81  
3.81  
7.79  
25.5

[illegible]

### CCM04-1889 PCB Layout

RECOMMENDED PC BOARD LAYOUT  
(Component side)

The diagram illustrates the recommended PCB layout for the CCM04-1889 component on the component side. Key features include:

- Plastic outline**: Indicated by a line pointing to the component's footprint.
- Contact foot area**: Labeled as 0,8 x 1.
- Pad**: A rectangular area with dimensions 5 x 2,54.
- Dimensions**: Various numerical values are provided for spacing and placement, including 15, 23,2, 5,5, 2,5, 5,5, 4,4, 1,5, 1,8, 5,69, 1,27, 13, 0,2, 7,99, 3,81, 3,81, 25,5, 4,4, and 10x.
- Component locations**: Labeled C5, C6, C7, C8, C1, C2, C3, C4, SW, and SW.
- Prohibited area**: Indicated by a line pointing to a specific region.
- Contact location according to ISO 7816-2**: A reference to the standard for contact locations.


Unless otherwise stated, tolerances are  $\pm 0.10$  mm

Unless otherwise stated, tolerances are  $\pm 0.10$  mm

# CCM04 MK II Low Profile


## Dimensional Drawings

CCM04-1905 2 x 8 contacts









## PCB Layout

CCM04-1905



# CCM04 MK II


## Dimensional Drawings




# CCM04 MK II

## Dimensional Drawings

CCM04-1317/1318/1319/1320 2 x 4 contacts plus switch




CCM04-1317/1318/1319/1320 PCB Layout




Unless otherwise stated, tolerances are  $\pm 0.10$  mm


CCM04-1334 2 x 8 contacts standard surface mount




CCM04-1334 PCB Layout



CCM04-5004/1201/1202/1203/1204 2x3 contacts standard surface mount




CCM04-5004\*/1201/1202/1203/1204 PCB Layout



Unless otherwise stated, tolerances are  $\pm 0.10$  mm

## CCM04 MK III Miniature Connectors



Introducing a new range of CCM04 connectors designed to interface with either full or SIM/SAM smart cards and designed to minimize space usage on the PCB while maximizing price economy.

### Features

- Available with 6 or 8 contacts.
- By using an inlay finish in the contact area, the life of the precious metal is extended by up to 10 times that of a standard gold plating.
- The contact area is spooned to reduce the risk of accidental (or deliberate) damage and to optimize the electrical connection with the card.
- The insulators, molded from high temperature thermoplastic, are suited for infrared and convection soldering processes.
- With tape and reel packaging as standard, the connectors are designed to be automatically pick and placed.
- Gold plating versions are also available.

### Construction

|                 |                                         |
|-----------------|-----------------------------------------|
| Insulator       | High temperature thermoplastic UL 94V.0 |
| Contacts        | Copper Alloy                            |
| Contact finish  | Gold Alloy Inlay (Au / Ag / Pd)         |
| PC Tail plating | Tin lead (2 $\mu$ m min) Sn / Pb        |

### Mechanical data

|                 |                                  |
|-----------------|----------------------------------|
| Mechanical life | 50,000 cycles minimum            |
| Precious metal  | 5000 cycles minimum (see note 1) |
| Contact force   | 0.25N min / 0.5N max             |
| Contact travel  | 0.75mm                           |

### Electrical data

|                        |                          |
|------------------------|--------------------------|
| Insulation resistance  | 1000 M $\Omega$ min      |
| Contact resistance max | 100 m $\Omega$ max       |
| Switching current      | 10 $\mu$ A min / 1 A max |
| Dielectric strength    | 500 Vrms min             |

### Environmental data

|                       |                                                                                    |
|-----------------------|------------------------------------------------------------------------------------|
| Operating temperature | -40°C to +85°C                                                                     |
| Soldering temperature | Temperature/time profile acc. to CECC00802 para. 6.1, Fig. 3 with peak temperature |
| Salt mist             | IEC 512 test number 11f (96 hours)                                                 |
| Damp heat             | IEC 512 test number 11c (10 days)                                                  |

# CCM04 MK III

## 6 Contacts Versions

| Part Number | N° of Contacts | Total Height | Total Length | Terminal Design | Contact Plating |      | Insulator Width | Packaging | Modification Code |
|-------------|----------------|--------------|--------------|-----------------|-----------------|------|-----------------|-----------|-------------------|
|             |                |              |              |                 | Inlay           | Gold |                 |           |                   |
| CCM04-4105  | 6              | 1.90         | 11.8         | SMT IN          | X               |      | 7.62            | 2400      | R242              |
| CCM04-5137  | 6              | 1.90         | 11.8         | SMT IN          |                 | X    | 7.62            | 2400      | R242              |
| CCM04-4118  | 6              | 1.90         | 14.3         | SMT OUT         | X               |      | 7.62            | 2400      | R242              |
| CCM04-5102* | 6              | 1.90         | 15.2         | SMT OUT         |                 | X    | 7.62            | 2400      | R242              |
| CCM04-5111  | 6              | 1.90         | 14.3         | SMT OUT         |                 | X    | 7.62            | 2400      | R242              |
| CCM04-4106  | 6              | 2.10         | 11.8         | SMT IN          | X               |      | 7.62            | 1900      | R192              |
| CCM04-5116  | 6              | 2.10         | 11.8         | SMT IN          |                 | X    | 7.62            | 1900      | R192              |
| CCM04-4119  | 6              | 2.10         | 14.3         | SMT OUT         | X               |      | 7.62            | 1900      | R192              |
| CCM04-5112  | 6              | 2.10         | 14.3         | SMT OUT         |                 | X    | 7.62            | 1900      | R192              |
| CCM04-4120  | 6              | 2.40         | 14.3         | SMT OUT         | X               |      | 7.62            | 1900      | R192              |
| CCM04-5120  | 6              | 2.40         | 14.3         | SMT OUT         |                 | X    | 7.62            | 1900      | R192              |
| CCM04-5106  | 6              | 2.50         | 11.8         | SMT IN          |                 | X    | 7.62            | 1900      | R192              |
| CCM04-5114  | 6              | 2.50         | 11.8         | SMT IN          | X               |      | 7.62            | 1900      | R192              |
| CCM04-4121  | 6              | 2.65         | 14.3         | SMT OUT         | X               |      | 7.62            | 1900      | R192              |
| CCM04-5121  | 6              | 2.65         | 14.3         | SMT OUT         |                 | X    | 7.62            | 1900      | R192              |
| CCM04-5115  | 6              | 2.80         | 11.8         | SMT IN          |                 | X    | 7.62            | 1900      | R192              |
| CCM04-5134  | 6              | 2.80         | 11.8         | SMT IN          | X               |      | 7.62            | 1900      | R192              |
| CCM04-4122* | 6              | 2.90         | 14.3         | SMT OUT         | X               |      | 7.62            | 1600      | R162              |
| CCM04-5122* | 6              | 2.90         | 14.3         | SMT OUT         |                 | X    | 7.62            | 1600      | R162              |

## 8 Contacts Versions

| Part Number | N° of Contacts | Total Height | Total Length | Terminal Design | Contact Plating |      | Insulator Width | Packaging | Modification Code |
|-------------|----------------|--------------|--------------|-----------------|-----------------|------|-----------------|-----------|-------------------|
|             |                |              |              |                 | Inlay           | Gold |                 |           |                   |
| CCM04-4135* | 8              | 1.90         | 11.8         | SMT IN          | X               |      | 10.16           | 2400      | R242              |
| CCM04-5123* | 8              | 1.90         | 11.8         | SMT IN          |                 | X    | 10.16           | 2400      | R242              |
| CCM04-4148* | 8              | 1.90         | 14.3         | SMT OUT         | X               |      | 10.16           | 2400      | R242              |
| CCM04-5129* | 8              | 1.90         | 14.3         | SMT OUT         |                 | X    | 10.16           | 2400      | R242              |
| CCM04-4136  | 8              | 2.10         | 11.8         | SMT IN          | X               |      | 10.16           | 1900      | R192              |
| CCM04-5113  | 8              | 2.10         | 11.8         | SMT IN          |                 | X    | 10.16           | 1900      | R192              |
| CCM04-4149  | 8              | 2.10         | 14.3         | SMT OUT         | X               |      | 10.16           | 1900      | R192              |
| CCM04-5130  | 8              | 2.10         | 14.3         | SMT OUT         |                 | X    | 10.16           | 1900      | R192              |
| CCM04-4150  | 8              | 2.40         | 14.3         | SMT OUT         | X               |      | 10.16           | 1900      | R192              |
| CCM04-5131  | 8              | 2.40         | 14.3         | SMT OUT         |                 | X    | 10.16           | 1900      | R192              |
| CCM04-5109  | 8              | 2.50         | 11.8         | SMT IN          | X               |      | 10.16           | 1900      | R192              |
| CCM04-5125  | 8              | 2.50         | 11.8         | SMT IN          |                 | X    | 10.16           | 1900      | R192              |
| CCM04-4151  | 8              | 2.65         | 14.3         | SMT OUT         | X               |      | 10.16           | 1900      | R192              |
| CCM04-5132  | 8              | 2.65         | 14.3         | SMT OUT         |                 | X    | 10.16           | 1900      | R192              |
| CCM04-5108  | 8              | 2.80         | 11.8         | SMT IN          | X               |      | 10.16           | 1900      | R192              |
| CCM04-5127  | 8              | 2.80         | 11.8         | SMT IN          |                 | X    | 10.16           | 1900      | R192              |
| CCM04-4152* | 8              | 2.90         | 14.3         | SMT OUT         | X               |      | 10.16           | 1600      | R162              |
| CCM04-5133* | 8              | 2.90         | 14.3         | SMT OUT         |                 | X    | 10.16           | 1600      | R162              |

Note: \*Versions on request



# CCM04 MK III

## 2 x 3 contacts SMT IN



| Height  | Inlay      | Gold       |
|---------|------------|------------|
| 1.90 mm | CCM04-4105 | CCM04-5137 |

| Height | Inlay      | Gold       |
|--------|------------|------------|
| 2.1 mm | CCM04-4106 | CCM04-5116 |

## Dimensional Drawings



## PCB Layout



Note: \* Versions on request



# CCM04 MK III

## 2 x 3 contacts SMT IN



| Height A | Height B | Inlay       | Gold        |
|----------|----------|-------------|-------------|
| 2.4 mm   | 0.5 mm   | CCM04-4107* | CCM04-5117* |
| 2.5 mm   | 0.6 mm   | CCM04-5114  | CCM04-5106  |
| 2.65 mm  | 0.75 mm  | CCM04-4108* | CCM04-5118* |
| 2.9 mm   | 1 mm     | CCM04-4109* | CCM04-5119* |
| 3.15 mm  | 1.25 mm  | CCM04-4110* | CCM04-5107* |

| Height | Inlay      | Gold       |
|--------|------------|------------|
| 2.8 mm | CCM04-5134 | CCM04-5115 |

## Dimensional Drawings



## PCB Layout



Note: \* Versions on request



Cannon

Dimensions are shown in mm  
Dimensions subject to change

[www.ittcannon.com](http://www.ittcannon.com)

## Dimensional Drawings

**2 x 3 contacts SMT OUT LONG**

|               |              |             |
|---------------|--------------|-------------|
| <b>Height</b> | <b>Inlay</b> | <b>Gold</b> |
| 1.9 mm        |              | CCM04-5102* |




[illegible][illegible]

ITT Industries

[www.ittcannon.com](http://www.ittcannon.com)

| Height  | Inlay      | Gold       |
|---------|------------|------------|
| 1.90 mm | CCM04-4135 | CCM04-5123 |

| Height | Inlay      | Gold       |
|--------|------------|------------|
| 2.1 mm | CCM04-4136 | CCM04-5113 |



| Height A | Height B | Inlay       | Gold        |
|----------|----------|-------------|-------------|
| 2.4 mm   | 0.5 mm   | CCM04-4137* | CCM04-5124* |
| 2.5 mm   | 0.6 mm   | CCM04-5109  | CCM04-5125  |
| 2.65 mm  | 0.75 mm  | CCM04-4138* | CCM04-5126* |
| 2.9 mm   | 1.0 mm   | CCM04-4139* | CCM04-5128* |
| 3.15 mm  | 1.25 mm  | CCM04-4140  | CCM04-5135* |

| Height | Inlay      | Gold       |
|--------|------------|------------|
| 2.8 mm | CCM04-5108 | CCM04-5127 |

11.8

1

10.15

0.25 0.05 x 4.6

Mated condition

3.81 3.81

SEE DETAIL A

A 0.05

11.5 0.2

Date Code area

11.5

10.15

127 REF1

0.75

19.05

25.4 25.4 25.4

25.4

0.7

0.13 A

26

DETAIL A

Scale 10

B REF1

0.8

11.5 (REF1)


25.4 25.4 25.4

25.4

Pick and place area

3.3

10.15



RECOMMENDED PC BOARD LAYOUT  
(Component side)


Plastic outline  
Contact foot area  
0,8 x 0,7  
Pad

Dimensions: 15, 8,85, 15, 25,4, 25,4, 25,4, 3,81, 3,81, 0,615, 11,15, 0,2, 1

Labels: C5, C6, C7, C8, C1, C2, C3, C4

Reference: 7816-2, 1375-1, GSM11

ISO 7816-2 & ENV 1375-1 & GSM11



ITT Industries


[www.ittcannon.com](http://www.ittcannon.com)

# CCM04 MK III


## 2 x 4 contacts SMT OUT

| Height A | Height B | Inlay       | Gold        |
|----------|----------|-------------|-------------|
| 1.9 mm   | 0.1 mm   | CCM04-4148  | CCM04-5129  |
| 2.1 mm   | 0.2 mm   | CCM04-4149  | CCM04-5130  |
| 2.4 mm   | 0.5 mm   | CCM04-4150  | CCM04-5131  |
| 2.65 mm  | 0.75 mm  | CCM04-4151  | CCM04-5132  |
| 2.9 mm   | 1.0 mm   | CCM04-4152* | CCM04-5133* |

## Dimensional Drawings



## PCB Layout



Note: \* Versions on request