




Micro Commercial Components
21201 Itasca Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

2N5832

Features

- Through Hole Package

Pin Configuration
Bottom View



Plastic-case Bipolar NPN Transistor

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Max	Units
OFF CHARACTERISTICS				
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage ($I_C=300\text{mA}$)	140		Vdc
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage	160		Vdc
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage	5.0		Vdc
I_{CBO}	Collector-Base Breakdown Current ($V_{CE}=120\text{Vdc}$)		50	nAdc

ON CHARACTERISTICS

h_{FE}	DC Current Gain* ($I_C=10\text{mA}$, $V_{CE}=5.0\text{Vdc}$)	175	500	
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ($I_C=10\text{mA}$)		0.2	Vdc


SMALL-SIGNAL CHARACTERISTICS

f_T	Current Gain-Bandwidth Product ($I_C=10\text{mA}$)	100		MHz
C_{ob}	Output Capacitance		4.0	pF
NF	Noise Figure		----	dB

Note: Maximum at typical JEDEC condition

$V_{(BR)CER}$ @ $R=10\text{ OHMS}$

TO-92



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.175	.185	4.45	4.70	
B	.175	.185	4.46	4.70	
C	.500	---	12.7	---	
D	.016	.020	0.41	0.63	
E	.135	.145	3.43	3.68	
G	.095	.105	2.42	2.67	