




THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

SIMPLEX FIBER OPTIC SC/APC TO SC/APC PATCH CORD							
PANDUIT PART NO.	BUFFERED FIBER				SC/APC CONNECTOR		
	RATING	FIBER TYPE	COUNT	COLOR	MAX. IL	RL	COLOR
F9B3A-3AM*	NO FLAME RATING	9/125um OSI	SIMPLEX 900um BUFFERED FIBER	BLUE	0.50dB	65dB	GREEN

* - DENOTES PATCH CORD LENGTH, WHERE M = METERS AND F = FEET

										SIMPLEX FIBER OPTIC PATCH CORD SC/APC TO SC/APC CONFIGURATION CUSTOMER DRAWING		
											 PANDUIT TM CORP. TINLEY PARK, ILL 60477	
										 THIRD ANGLE PROJECTION	ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: (.X) (.XXX) ± .010 (0.3) (.XX) ± .03 (0.8) ANGLES	
											DRAWING FILENAME M02779CM_DC_00A.prt	
											SCALE NONE	
										DRAWN BY MC	REVIEW DRAWING NUMBERS	
											PART NO. SEE TABLE	
R	06-14-07	MC		RELEASED TO PRODUCTION	02779-42					DATE 06-08-07	DRAWING NO. 02779-42 (SHT. 2 of 2)	
REV	DATE	BY	CHK	DESCRIPTION	ECN	R	CUST	SUP	OTH	CHK'D	SIZE A	