

MLG1005S1N8ST000

Applications		Commercial Grade
Feature		Multilayer
		Non-Magnetic Core (Dielectric Ceramic)
Series	MLG Series / MLG1005S Type	
Status	PROD	




Size	
Length(L)	1.00mm +/-0.05mm
Width(W)	0.50mm +/-0.05mm
Thickness(T)	0.50mm +/-0.05mm
Recommended Land Pattern (A)	0.50mm Nom.
Recommended Land Pattern (B)	0.40mm Nom.
Recommended Land Pattern (C)	0.50mm Nom.

Electrical Characteristics	
Inductance	1.8nH +/-0.3nH at 100MHz
Rated Current (Temperature Rise) [Max.]	900mA (20degC Rise)
Self-Resonant Frequency [Min.]	8GHz
Self-Resonant Frequency [Typ.]	10.3GHz
Q [Min.]	7 at 100MHz
Q [Typ.]	11 at 100MHz
DC Resistance [Nom.]	60mΩ
DC Resistance [Max.]	150mΩ


Other	
Operating Temp. Range (Including Self-Temp. Rise)	-55 to 125degC
Soldering Method	Reflow, Iron Soldering
AEC Q200	No
Packing	Punched (Paper)Taping [180mm Reel]
Package Quantity	10000Pcs Min.
Weight	0.001g

MLG1005S1N8ST000

Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)




MLG1005S1N8ST000



MLG1005S1N8ST000



MLG1005S1N8ST000



MLG1005S1N8ST000

•This PDF document was created based on the data listed on the TDK Corporation website.

•All specifications are subject to change without notice.

MLG1005S1N8ST000

Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)

DC Bias Characteristic

no data available

Temperature Characteristic

no data available

Temperature Rise by DC

no data available