

PRODUCT DATA SHEET

Optical Transceiver: 1000M-SFP-M

Description:

1000M-SFP-M is multi-vendor compatible SFP Transceiver module, operating over Cat. 5 or Cat. 6 Twisted pair cooper cable with maximum distance of 100m. 1000M-SFP-M supports 1000Mbps data rate.

1000M-SFP-M SFP Transceiver is fully compliant to SFP Multi Source Agreement SFF-8472 and it can be provided with custom-encoded firmware, in order to provide compatibility of most equipment vendors platforms in data communications industry.

Key Highlights:

Type: SFP

Media Type: Twisted Pair Cable

Max. Distance: 100m

• Data Rate: 1000 Mbps

Temperature: Standard 0°-70°C



TECHNICAL SPECIFICATION

Parameter	Value
Product Type:	1000M-SFP-M
Media Type:	Cat.5 Cat.6 Twisted Pair
Maximum Distance:	100 m
Supported Data Rate:	1000 Mbps
Supported Applications:	Ethernet (10 Mbps)Fast Ethernet (100 Mbps)Gigabit Ethernet (1000 Mbps)
Temperature Range:	Standard 0°-70°C
Connectors:	RJ45
Chip:	Marvel, Maxim
Power:	+3.3V single power supply
Compliance:	SFP MSA,IEEE STD 802.3,802.3ab,RoHS,CE



Compatibility

EDGE Optical transceivers can be provided with custom-encoded firmware, in order to provide compatibility with more then 50 vendor brands in data and telecom communications industry:

MS - General MSA

AD - ADVA

AL - Alcatel-Lucent

AR - Arista

AV - Avaya

BR - Brocade

CN - Ciena

CI - Cisco

DL - Dell & Force10

DK - D-Link

EM - EMC2

ET - Enterasys

ER - Ericsson

EX - Extreme Networks

F5 - F5 Networks

FO - Fortinet

FU - Fujitsu H3 - H3C

HI - Hirschmann

HP* - HP Networking

HS* - HP Storage

HU - Huawei

IB - IBM

IF - Infinera

IN - Intel

JU - Juniper Networks

LI - Linksys

ML - Mellanox

ME - Meraki (Cisco)

MT - MikroTik

MO - Moxa

MR - MRV

NG - Netgear

NS - NSN

PA - Palo Alto Network

QL - Qlogic

RD - RAD

RU - Ruijie Networks

SM - Supermicro

SY - Synology

TC - Telco Systems

TP - TP-LINK

TN - Trendnet

WG - WatchGuard

ZT - ZTE

XX - Other

Product Quality

We focus on strict product quality tests before each delivery, performing optical parameter tests, connector cleanliness tests and firmware verification tests to ensure our delivered products fully meets the promised product technical specification and compatibility requirements.

EDGE Optical transceivers are CE, ROHS certified and have passed Telecordia reliability tests.

Warranty

EDGE Optic's provides a limited **warranty for sixty (60) months** from Purchaser's receipt of the Equipment represented in this data sheet against defective design or workmanship.



^{* -} Please note HP compatible module prices can be higher then prices indicated in this material due to special requirements in coding. If you require HP compatibility, for exact pricing please contact our sales team: sales@edgeoptic.com